

屋内照明器具特性	
品番 (品名)	L G B 1 5 1 0 6
光源	L L D 2 0 0 0 1 C Q 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 8 6 4 8 8 (0) D R 1
B Z 分類	B Z 5

器具効率		7 9 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
						室指数	照明率 (X 0 . 0 1) Z C M															
保守率		良 中 否	0 . 6 7	0 . 6	4 3	3 4	2 7	2 3	4 2	3 3	2 7	2 3	4 0	3 2	2 6	2 3	3 8	3 1	2 6	2 2	2 0	
			0 . 6 3	0 . 8	5 1	4 2	3 6	3 1	5 0	4 1	3 5	3 1	4 7	4 0	3 4	3 0	4 5	3 8	3 3	3 0	2 8	
			1 . 0	1 . 0	5 6	4 8	4 1	3 7	5 5	4 7	4 1	3 6	5 2	4 5	4 0	3 6	4 9	4 3	3 9	3 5	3 3	
			0 . 5 6	1 . 2 5	6 1	5 3	4 7	4 3	5 9	5 2	4 7	4 2	5 6	5 0	4 5	4 1	5 4	4 8	4 4	4 1	3 8	
下方投影面積		c m ²	1 . 5	6 4	5 7	5 1	4 7	6 3	5 6	5 1	4 6	6 0	5 4	4 9	4 6	5 7	5 2	4 8	4 5	4 2		
			2 . 0	6 9	6 3	5 8	5 4	6 7	6 2	5 7	5 3	6 4	5 9	5 5	5 2	6 1	5 7	5 4	5 1	4 8		
等価発光面積		c m ²	2 . 5	7 2	6 6	6 2	5 8	7 0	6 5	6 1	5 8	6 7	6 3	5 9	5 6	6 4	6 1	5 8	5 5	5 2		
			3 . 0	7 4	6 9	6 5	6 2	7 2	6 8	6 4	6 1	6 9	6 5	6 2	5 9	6 6	6 3	6 0	5 8	5 5		
H m	1 . 1 7 H m	1 . 1 7 H m	4 . 0	7 6	7 3	6 9	6 6	7 5	7 1	6 8	6 6	7 2	6 9	6 6	6 4	6 9	6 6	6 4	6 2	5 9		
			5 . 0	7 8	7 5	7 2	7 0	7 6	7 4	7 1	6 9	7 3	7 1	6 9	6 7	7 0	6 8	6 7	6 5	6 2		
			7 . 0	8 0	7 7	7 5	7 3	7 8	7 6	7 4	7 2	7 5	7 3	7 2	7 0	7 2	7 1	7 0	6 8	6 5		
			1 0 . 0	8 1	7 9	7 8	7 6	8 0	7 8	7 7	7 5	7 7	7 5	7 4	7 3	7 4	7 3	7 2	7 1	6 8		

