

屋内照明器具特性	
品番 (品名)	LGB15107
光源	LLD3020LCE1 ×1 795.0 l m
管理番号	K0176232 (0) DR 1
B Z 分類	BZ1

器具効率		65 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %					
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %				10 %				10 %				10 %				0 %					
上方光束		0 %	室指数	照明率 (X0.01)																				Z	C	M
下方光束		65 %																								
保守率		良 中 否	0.67	0.6	53	49	46	44	53	49	46	44	52	48	46	44	51	48	46	44	43					
			0.63	0.8	57	53	51	49	57	53	50	49	55	52	50	48	54	52	50	48	47					
			0.56	1.0	60	56	53	52	59	56	53	51	58	55	53	51	57	54	52	51	50					
			1.25	62	59	56	54	61	58	56	54	60	57	55	54	59	57	55	53	52						
下方投影面積		c m ²	1.5	63	60	58	56	62	60	58	56	61	59	57	56	60	58	57	55	54						
等価発光面積			c m ²	2.0	65	63	61	59	64	62	60	59	63	61	60	58	62	60	59	58	56					
取付 高さ	器具間隔最大限		2.5	66	64	62	61	65	63	62	61	64	62	61	60	63	61	60	59	58						
	横方向 (A)		縦方向 (B)	3.0	67	65	64	62	66	64	63	62	65	63	62	61	63	62	61	60	59					
H m	0.45 H m	0.45 H m	4.0	68	66	65	64	67	66	65	64	66	65	64	63	64	63	63	62	60						
			5.0	68	67	66	65	68	67	66	65	66	65	65	64	65	64	63	63	61						
			7.0	69	68	67	67	68	68	67	66	67	66	66	65	65	65	64	64	62						
			10.0	70	69	68	68	69	68	68	67	67	67	66	66	66	66	65	65	63						

