

屋内照明器具特性

品番 (品名)	S C 8 0 1 W K	
光源	LDA4L-G-E17/Z40E/S/W/2 x1	440.0 lm
管理番号	K0131311(0)DR1	
BZ分類	BZ10/0.7/BZ9/1.8/BZ10/2.3/BZ9/2.8/BZ1	

器具効率	86%	天井	80%				70%				50%				30%				0%					
	上方光束		52%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
	下方光束		34%	壁	10%				10%				10%				10%				0%			
室指数	照明率 (X0.01)																			ZCM				
保守率	良	0.63	0.6	0.56	0.6	3.7	2.7	2.0	1.6	3.4	2.4	1.8	1.4	2.6	1.9	1.5	1.1	2.0	1.5	1.1	0.8	0.3		
	中	0.6	0.6	0.56	0.6	4.4	3.4	2.7	2.2	4.0	3.1	2.4	2.0	3.1	2.4	1.9	1.6	2.4	1.8	1.5	1.2	0.5		
	否	0.56	0.6	0.56	0.6	4.9	3.9	3.2	2.7	4.4	3.5	2.9	2.4	3.5	2.8	2.3	1.9	2.6	2.1	1.8	1.5	0.7		
下方投影面積	cm ²		1.25	1.5	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	10.0	12.5	15	20	25	30	40	50	60	70	80	
	等価発光面積		cm ²	1.5	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	10.0	12.5	15	20	25	30	40	50	60	70	80	
取付高さ	器具間隔最大限		Hm		Hm		Hm		Hm		Hm		Hm		Hm		Hm		Hm		Hm		Hm	
	横方向 (A)	縦方向 (B)	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
取付高さ	器具間隔最大限		Hm		Hm		Hm		Hm		Hm		Hm		Hm		Hm		Hm		Hm		Hm	
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
5.0	7.0	10.0	7.5	7.1	6.8	6.5	6.2	6.0	5.5	5.3	5.1	4.9	4.4	4.2	4.0	3.9	3.7	3.6	3.5	3.3	3.2	3.0	2.7	2.1
7.0	7.5	10.0	7.5	7.1	6.8	6.5	6.2	6.0	5.5	5.3	5.1	4.9	4.4	4.2	4.0	3.9	3.7	3.6	3.5	3.3	3.2	3.0	2.7	2.1
10.0	7.6	7.4	7.1	6.9	7.0	6.8	6.5	6.3	5.7	5.5	5.4	5.2	4.5	4.4	4.3	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	2.6

