

屋内照明器具特性	
品番(品名)	LGB84080Z
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 1 m
管理番号	K0170217(0)DR1
BZ分類	BZ6/0.7/BZ5/3.5/BZ4

器具効率	78%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	78%	室指数	照明率 ( X0.01 )																ZCM	
保守率	良 中 否 0.67 0.63 0.56	0.6	42	32	26	22	41	32	26	22	39	31	25	21	38	30	25	21	20	
		0.8	51	41	35	30	50	41	35	30	47	40	34	30	45	39	34	30	28	
		1.0	56	48	42	37	55	47	41	37	53	46	41	36	51	45	40	36	34	
		1.25	61	54	48	43	60	53	47	43	58	52	47	43	56	50	46	42	41	
下方投影面積	c m <sup>2</sup>	1.5	65	58	53	48	64	57	52	48	61	56	51	47	59	54	50	47	45	
		2.0	70	64	59	55	68	63	59	55	66	61	58	54	64	60	57	54	52	
取付高さ	器具間隔最大限		2.5	73	68	64	60	71	67	63	60	69	65	62	59	67	64	61	58	56
	横方向(A)	縦方向(B)	3.0	75	70	67	64	73	69	66	63	71	68	65	62	69	66	64	61	59
H m	1.49 H m	1.49 H m	4.0	77	74	71	68	76	73	70	68	74	71	69	67	72	69	68	66	64
			5.0	79	76	73	71	77	75	73	71	75	73	71	69	73	72	70	68	66
			7.0	80	78	76	75	79	77	76	74	77	76	74	73	75	74	73	72	69
			10.0	82	80	79	77	81	79	78	77	79	77	76	75	77	76	75	74	72

