

屋内照明器具特性	
品番 (品名)	L G B 1 5 1 0 7
光源	L L D 2 0 0 0 C U 1 × 1 5 6 6 . 0 l m
管理番号	K 0 1 7 8 7 2 7 (0) D R 1
B Z 分類	B Z 5

器具効率		6 7 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	3 8	3 0	2 5	2 2	3 7	3 0	2 5	2 1	3 5	2 9	2 4	2 1	3 4	2 8	2 4	2 1	1 9
			0 . 6 3	0 . 8	4 5	3 7	3 2	2 8	4 4	3 7	3 2	2 8	4 2	3 5	3 1	2 8	4 0	3 4	3 0	2 7	2 6
			0 . 5 6	1 . 0	4 9	4 2	3 7	3 3	4 8	4 1	3 7	3 3	4 6	4 0	3 6	3 2	4 4	3 9	3 5	3 2	3 0
				1 . 2 5	5 3	4 7	4 2	3 8	5 2	4 6	4 1	3 8	4 9	4 4	4 0	3 7	4 7	4 3	3 9	3 7	3 5
下方投影面積		c m ²	1 . 5	5 6	5 0	4 5	4 2	5 4	4 9	4 5	4 1	5 2	4 7	4 4	4 1	5 0	4 6	4 3	4 0	3 8	
			等価発光面積	2 . 0	5 9	5 5	5 1	4 7	5 8	5 4	5 0	4 7	5 6	5 2	4 9	4 6	5 3	5 0	4 7	4 5	4 3
取付高さ	器具間隔最大限		2 . 5	6 2	5 8	5 4	5 1	6 0	5 7	5 3	5 0	5 8	5 5	5 2	4 9	5 6	5 3	5 1	4 8	4 6	
	横方向 (A) 縦方向 (B)		3 . 0	6 3	6 0	5 7	5 4	6 2	5 9	5 6	5 3	6 0	5 7	5 4	5 2	5 7	5 5	5 3	5 1	4 9	
H m	0 . 8 2 H m	0 . 8 2 H m	4 . 0	6 5	6 2	6 0	5 8	6 4	6 1	5 9	5 7	6 2	6 0	5 7	5 6	6 0	5 8	5 6	5 4	5 2	
			5 . 0	6 7	6 4	6 2	6 0	6 5	6 3	6 1	5 9	6 3	6 1	5 9	5 8	6 1	5 9	5 8	5 7	5 4	
			7 . 0	6 8	6 6	6 5	6 3	6 7	6 5	6 4	6 2	6 5	6 3	6 2	6 1	6 2	6 1	6 0	5 9	5 7	
			1 0 . 0	6 9	6 8	6 7	6 5	6 8	6 7	6 6	6 5	6 6	6 5	6 4	6 3	6 4	6 3	6 2	6 1	5 9	

