

屋内照明器具特性	
品番 (品名)	LGB15107
光源	LLD2020CU1 ×1 468.0 lm
管理番号	K0178730 (0) DR1
BZ分類	BZ1

器具効率		60 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束		60 %																						
保守率		良	0.67	0.6	49	45	42	40	48	44	42	40	47	44	42	40	47	44	42	40	40			
		中	0.63	0.8	52	49	46	44	52	48	46	44	51	48	46	44	50	47	45	44	43			
		否	0.56	1.0	54	51	49	47	54	51	49	47	53	50	48	47	52	50	48	47	46			
		1.25	56	53	51	50	56	53	51	49	55	52	51	49	54	52	50	49	48					
下方投影面積		c m ²		1.5	58	55	53	51	57	55	53	51	56	54	52	51	55	53	52	50	50			
等価発光面積		c m ²		2.0	59	57	55	54	59	57	55	54	57	56	54	53	56	55	54	53	52			
取付 高さ	器具間隔最大限			2.5	60	59	57	56	60	58	57	55	58	57	56	55	57	56	55	54	53			
	横方向 (A)		縦方向 (B)	3.0	61	60	58	57	60	59	58	57	59	58	57	56	58	57	56	55	54			
H m	0.45 H m	0.45 H m	4.0	62	61	60	59	61	60	59	58	60	59	58	57	59	58	57	57	55				
			5.0	62	61	61	60	62	61	60	59	60	60	59	58	59	59	58	57	56				
			7.0	63	62	62	61	62	62	61	60	61	60	60	59	60	59	59	58	57				
			10.0	64	63	62	62	63	62	62	61	62	61	61	60	60	60	60	59	58				

