

# 屋内照明器具特性

品番 (品名)	LGBZ6110	
光源	LED6200_70_3400 ×1	3400.0 lm
管理番号	K0166869(0)D 1	
BZ分類	BZ6/0.7/BZ5/3.5/BZ6/4.5/BZ5 /6.0/BZ6	

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束 19%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
下方光束	81%	床		10%				10%				10%				10%				0%	
室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.63	0.6	5.2	4.0	3.2	2.7	5.0	3.9	3.1	2.6	4.6	3.6	3.0	2.5	4.2	3.4	2.8	2.4	2.1	
	中	0.6	0.8	6.2	5.0	4.2	3.6	5.9	4.8	4.0	3.5	5.4	4.5	3.8	3.3	4.9	4.2	3.6	3.2	2.8	
	否	0.56	1.0	6.8	5.7	4.9	4.3	6.5	5.5	4.7	4.2	6.0	5.1	4.5	4.0	5.5	4.7	4.2	3.8	3.3	
			1.25	7.4	6.3	5.6	4.9	7.0	6.1	5.4	4.8	6.5	5.7	5.1	4.6	5.9	5.3	4.8	4.4	3.9	
下方投影面積	cm <sup>2</sup>		1.5	7.8	6.8	6.1	5.5	7.4	6.6	5.9	5.3	6.8	6.1	5.6	5.1	6.3	5.7	5.2	4.8	4.3	
等価発光面積	cm <sup>2</sup>		2.0	8.3	7.5	6.8	6.3	8.0	7.3	6.6	6.1	7.4	6.8	6.2	5.8	6.8	6.3	5.9	5.5	4.9	
取付高さ	器具間隔最大限		2.5	8.7	8.0	7.4	6.9	8.3	7.7	7.1	6.7	7.7	7.2	6.7	6.3	7.1	6.7	6.3	6.0	5.3	
	横方向 (A)	縦方向 (B)	3.0	8.9	8.3	7.8	7.3	8.6	8.0	7.5	7.1	8.0	7.5	7.1	6.7	7.4	7.0	6.6	6.3	5.7	
H <sub>m</sub>	1.28H <sub>m</sub>	1.27H <sub>m</sub>	4.0	9.3	8.7	8.3	7.9	8.9	8.5	8.0	7.7	8.3	7.9	7.6	7.2	7.7	7.4	7.1	6.8	6.1	
			5.0	9.5	9.0	8.6	8.3	9.1	8.7	8.4	8.0	8.5	8.2	7.9	7.6	7.9	7.6	7.4	7.2	6.4	
			7.0	9.7	9.4	9.1	8.8	9.4	9.1	8.8	8.5	8.7	8.5	8.3	8.0	8.1	7.9	7.7	7.6	6.8	
			10.0	9.9	9.7	9.4	9.2	9.6	9.3	9.1	8.9	8.9	8.8	8.6	8.4	8.3	8.2	8.0	7.9	7.1	

