

# 屋内照明器具特性

品番 (品名)	LGBZ8112	
光源	LED6200_70_4700 x1      4700.0 lm	
管理番号	K0164173(0)D 1	
BZ分類	BZ4	

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		21%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		79%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.63	0.6	55	44	36	31	53	42	36	31	49	40	34	29	45	37	32	28	25	
	中	0.6	0.8	65	54	47	41	62	52	46	41	57	49	43	39	53	46	41	37	33	
	否	0.56	1.0	71	61	54	49	68	59	53	48	63	55	50	45	58	52	47	43	39	
			1.25	77	68	61	56	74	66	60	55	68	61	56	52	63	57	53	49	44	
下方投影面積	cm <sup>2</sup>		1.5	81	73	67	61	78	70	65	60	72	66	61	57	66	61	57	54	48	
	等価発光面積		cm <sup>2</sup>	2.0	86	80	74	69	83	77	72	68	77	72	68	64	71	67	63	61	54
取付高さ	器具間隔最大限		2.5	90	84	79	75	86	81	77	73	80	76	72	69	74	70	67	65	58	
	横方向 (A)	縦方向 (B)	3.0	92	87	83	79	88	84	80	77	82	78	75	72	76	73	70	68	61	
Hm	1.24Hm	1.25Hm	4.0	95	91	87	84	91	88	85	82	85	82	79	77	78	76	74	72	65	
			5.0	96	93	90	88	93	90	87	85	86	84	82	80	80	78	77	75	67	
			7.0	98	96	94	92	95	93	91	89	88	87	85	83	82	81	79	78	70	
			10.0	100	98	97	95	97	95	93	92	90	89	87	86	84	83	82	81	72	

