

屋内照明器具特性	
品番 (品名)	LGB15108
光源	LLD40001CQ1 ×1 845.0 lm
管理番号	K0186496 (0) DR1
BZ分類	BZ4/1.4/BZ5

器具効率		47 %	反射率	天井	80 %				70 %				50 %				30 %				0 %					
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %				10 %				10 %				10 %				0 %					
上方光束		1 %	室指数	照明率 (X0.01)																			Z	C		M
下方光束		46 %																								
保守率		良 中 否	0.67	0.6	28	22	19	16	27	22	19	16	26	21	18	16	25	21	18	16	15					
			0.63	0.8	32	27	23	21	31	26	23	21	30	26	23	20	29	25	22	20	19					
			0.56	1.0	35	30	26	24	34	30	26	24	33	29	26	23	31	28	25	23	22					
				1.25	38	33	30	27	37	33	29	27	35	32	29	27	34	31	28	26	25					
下方投影面積		cm ²	1.5	39	35	32	30	39	35	32	29	37	34	31	29	35	33	30	29	27						
等価発光面積		cm ²	2.0	42	38	36	33	41	38	35	33	39	37	34	33	38	36	34	32	31						
取付 高さ	器具間隔最大限		2.5	44	41	38	36	43	40	38	36	41	39	37	35	40	38	36	34	33						
	横方向 (A)		縦方向 (B)		3.0	45	42	40	38	44	41	39	38	42	40	38	37	41	39	38	36	35				
H m	0.85 H m		0.85 H m		4.0	46	44	42	41	45	43	42	40	44	42	41	39	42	41	40	39	37				
					5.0	47	45	44	42	46	45	43	42	45	43	42	41	43	42	41	40	39				
					7.0	48	47	46	44	47	46	45	44	46	45	44	43	44	44	43	42	40				
					10.0	49	48	47	46	48	47	46	46	47	46	45	45	45	45	44	43	42				

