

屋内照明器具特性	
品番 (品名)	L G B 1 5 1 0 8
光源	LLD4000LCT1 ×1 845.0 l m
管理番号	K0190501 (0) DR 1
B Z 分類	BZ5 / 0.7 / BZ4 / 2.3 / BZ5

器具効率		43 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束 下方光束		2 % 41 %	室指数	照明率 (X0.01) Z C M																		
保守率		良 中 否	0.67	0.6	24	19	16	14	24	19	16	14	23	19	16	14	22	18	15	14	13	
			0.63	0.8	29	24	21	18	28	23	20	18	27	23	20	18	25	22	20	18	17	
			1.0	31	27	24	21	31	26	23	21	29	26	23	21	28	25	22	21	19		
			0.56	1.25	34	30	27	24	33	29	26	24	31	28	26	24	30	27	25	23	22	
下方投影面積 等価発光面積		c m ² c m ²	1.5	35	32	29	27	35	31	29	26	33	30	28	26	32	29	27	26	24		
			2.0	38	35	32	30	37	34	32	30	35	33	31	29	34	32	30	29	27		
取付 高さ	器具間隔最大限		2.5	39	37	34	32	38	36	34	32	37	35	33	32	35	34	32	31	30		
	横方向 (A) 縦方向 (B)		3.0	40	38	36	34	39	37	35	34	38	36	35	33	36	35	34	32	31		
H m	0.85 H m 0.85 H m		4.0	41	40	38	37	41	39	38	36	39	38	37	35	38	37	36	35	33		
			5.0	42	41	39	38	41	40	39	38	40	39	38	37	39	38	37	36	34		
			7.0	43	42	41	40	42	41	40	40	41	40	39	39	40	39	38	38	36		
			10.0	44	43	42	42	43	42	42	41	42	41	41	40	40	40	39	39	37		

