

屋内照明器具特性	
品番 (品名)	L G B 1 5 1 5 0
光源	L L D 4 0 0 0 L C B 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 7 6 2 5 8 (0) D R 1
B Z 分類	B Z 4 / 2 . 3 / B Z 5

器具効率		47 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		1 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束		46 %																						
保守率		良 中 否	0.67	0.6	28	22	19	16	27	22	19	16	26	22	18	16	25	21	18	16	15			
			0.63	0.8	32	27	23	21	31	27	23	21	30	26	23	21	29	25	22	20	19			
			0.56	1.0	35	30	27	24	34	30	26	24	33	29	26	24	31	28	25	23	22			
			1.25	38	33	30	27	37	33	30	27	35	32	29	27	34	31	28	27	25				
下方投影面積 等価発光面積		cm ² cm ²	1.5	40	36	32	30	39	35	32	30	37	34	31	29	36	33	31	29	28				
			2.0	42	39	36	34	41	38	36	33	40	37	35	33	38	36	34	32	31				
			2.5	44	41	38	36	43	40	38	36	41	39	37	35	40	38	36	35	33				
取付 高さ	器具間隔最大限		3.0	45	42	40	38	44	42	40	38	42	40	39	37	41	39	38	36	35				
	横方向 (A)	縦方向 (B)	4.0	46	44	42	41	45	44	42	40	44	42	41	40	42	41	40	39	37				
H m	1.00 H m	1.00 H m	5.0	47	45	44	42	46	45	43	42	45	43	42	41	43	42	41	40	39				
			7.0	48	47	46	45	47	46	45	44	46	45	44	43	44	44	43	42	40				
			10.0	49	48	47	46	48	47	46	46	47	46	45	45	45	45	44	44	42				

