

屋内照明器具特性	
品番 (品名)	L G B 1 5 1 5 0
光源	L L D 3 0 2 0 L C B 1 × 1 7 9 5 . 0 l m
管理番号	K 0 1 7 6 2 6 1 (0) D R 1
B Z 分類	B Z 1

器具効率			6 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %					
					壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %					
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %					
上方光束			0 %	室指数	照明率 (X 0 . 0 1)																			Z C M			
下方光束			6 0 %																								
保守率			良	0 . 6 7	0 . 6	4 9	4 5	4 2	4 1	4 9	4 5	4 2	4 1	4 8	4 4	4 2	4 1	4 7	4 4	4 2	4 0	4 0					
			中	0 . 6 3	0 . 8	5 3	4 9	4 7	4 5	5 2	4 9	4 7	4 5	5 1	4 8	4 6	4 5	5 0	4 8	4 6	4 5	4 4					
			否	0 . 5 6	1 . 0	5 5	5 2	4 9	4 8	5 4	5 1	4 9	4 8	5 3	5 1	4 9	4 7	5 2	5 0	4 9	4 7	4 6					
						1 . 2 5	5 7	5 4	5 2	5 0	5 6	5 4	5 2	5 0	5 5	5 3	5 1	5 0	5 4	5 2	5 1	5 0	4 9				
下方投影面積			c m ²	1 . 5	5 8	5 6	5 4	5 2	5 8	5 5	5 3	5 2	5 7	5 5	5 3	5 2	5 5	5 4	5 2	5 1	5 0						
				2 . 0	6 0	5 8	5 6	5 5	5 9	5 7	5 6	5 5	5 8	5 7	5 5	5 4	5 7	5 6	5 4	5 3	5 2						
等価発光面積			c m ²	2 . 5	6 1	5 9	5 8	5 6	6 0	5 9	5 7	5 6	5 9	5 8	5 7	5 6	5 8	5 7	5 6	5 5	5 4						
				3 . 0	6 2	6 0	5 9	5 8	6 1	6 0	5 8	5 7	6 0	5 9	5 8	5 7	5 9	5 8	5 7	5 6	5 5						
H m	0 . 4 9 H m		0 . 4 9 H m	4 . 0	6 3	6 1	6 0	5 9	6 2	6 1	6 0	5 9	6 1	6 0	5 9	5 8	5 9	5 9	5 8	5 7	5 6						
				5 . 0	6 3	6 2	6 1	6 0	6 2	6 2	6 1	6 0	6 1	6 0	6 0	5 9	6 0	5 9	5 9	5 8	5 7						
				7 . 0	6 4	6 3	6 2	6 2	6 3	6 2	6 2	6 1	6 2	6 1	6 1	6 0	6 0	6 0	6 0	5 9	5 8						
				1 0 . 0	6 4	6 4	6 3	6 3	6 3	6 3	6 3	6 2	6 2	6 2	6 1	6 1	6 1	6 1	6 0	6 0	5 8						

