

屋内照明器具特性	
品番 (品名)	L G B 1 5 1 5 0
光源	LLD2000LCE1 ×1 531.0 l m
管理番号	K0176259 (0) DR 1
B Z 分類	BZ4 / 2.3 / BZ5

器具効率		63 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.67	0.6	37	30	25	22	36	30	25	22	35	29	25	22	33	28	24	22	20
			0.63	0.8	43	36	31	28	42	36	31	28	40	35	31	28	38	34	30	27	26
			1.0	47	40	36	32	46	40	35	32	44	39	35	32	42	38	34	31	30	
			0.56	1.25	50	45	40	37	49	44	40	36	47	43	39	36	45	41	38	36	34
下方投影面積		c m ²	1.5	53	48	43	40	52	47	43	40	50	45	42	39	48	44	41	39	37	
			2.0	56	52	48	45	55	51	47	45	53	49	46	44	51	48	45	43	41	
等価発光面積		c m ²	2.5	58	54	51	48	57	54	51	48	55	52	49	47	53	50	48	46	44	
			3.0	60	56	54	51	59	56	53	50	57	54	52	50	55	52	50	49	47	
H m	1.00 H m	1.00 H m	4.0	62	59	57	54	61	58	56	54	59	56	55	53	57	55	53	52	50	
			5.0	63	61	59	57	62	60	58	56	60	58	56	55	58	56	55	54	52	
			7.0	64	63	61	60	63	62	60	59	61	60	59	58	59	58	57	56	54	
			10.0	65	64	63	62	64	63	62	61	62	61	60	60	60	60	59	58	56	

