

屋内照明器具特性	
品番 (品名)	L G B 1 5 1 5 1
光源	L L D 2 0 2 0 M L C E 1 × 1 4 6 0 . 0 l m
管理番号	K 0 1 7 6 2 8 0 (0) D R 1
B Z 分類	B Z 1

器具効率			7 9 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
					壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束			0 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束			7 9 %																					
保守率			良 中 否	0 . 6 7	0 . 6	6 5	6 0	5 7	5 5	6 5	6 0	5 7	5 5	6 4	5 9	5 7	5 5	6 3	5 9	5 6	5 4	5 4		
				0 . 6 3	0 . 8	7 0	6 5	6 2	6 0	6 9	6 5	6 2	6 0	6 8	6 4	6 2	6 0	6 7	6 4	6 1	6 0	5 9		
				0 . 5 6	1 . 0	7 3	6 9	6 6	6 4	7 2	6 8	6 6	6 4	7 1	6 8	6 5	6 3	7 0	6 7	6 5	6 3	6 2		
				1 . 2 5	7 6	7 2	6 9	6 7	7 5	7 1	6 9	6 7	7 3	7 0	6 8	6 6	7 2	7 0	6 8	6 6	6 5			
下方投影面積			c m ²	1 . 5	7 7	7 4	7 1	6 9	7 6	7 3	7 1	6 9	7 5	7 2	7 0	6 9	7 3	7 1	7 0	6 8	6 7			
				2 . 0	7 9	7 7	7 4	7 3	7 8	7 6	7 4	7 2	7 7	7 5	7 3	7 2	7 5	7 4	7 2	7 1	7 0			
取付 高さ		器具間隔最大限		2 . 5	8 1	7 8	7 6	7 5	8 0	7 8	7 6	7 4	7 8	7 6	7 5	7 4	7 7	7 5	7 4	7 3	7 1			
		横方向 (A)	縦方向 (B)	3 . 0	8 2	8 0	7 8	7 6	8 1	7 9	7 7	7 6	7 9	7 7	7 6	7 5	7 7	7 6	7 5	7 4	7 2			
H m	0 . 5 0 H m	0 . 5 0 H m	4 . 0	8 3	8 1	8 0	7 8	8 2	8 0	7 9	7 8	8 0	7 9	7 8	7 7	7 8	7 7	7 7	7 6	7 4				
			5 . 0	8 3	8 2	8 1	8 0	8 2	8 1	8 0	7 9	8 1	8 0	7 9	7 8	7 9	7 8	7 8	7 7	7 5				
			7 . 0	8 4	8 3	8 2	8 1	8 3	8 2	8 1	8 1	8 1	8 1	8 0	7 9	8 0	7 9	7 9	7 8	7 6				
			1 0 . 0	8 5	8 4	8 3	8 3	8 4	8 3	8 2	8 2	8 2	8 1	8 1	8 0	8 0	8 0	7 9	7 9	7 7				

