

屋内照明器具特性	
品番 (品名)	LGB15151
光源	LLD2020CU1 ×1 468.0 lm
管理番号	K0178746 (0) DR1
BZ分類	BZ1

器具効率		60 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %					
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %				10 %				10 %				10 %				0 %					
上方光束		0 %	室指数	照明率 (X0.01)																			Z	C		M
下方光束		60 %																								
保守率		良	0.67	0.6	49	45	43	41	49	45	43	41	48	45	42	41	47	44	42	41	40					
		中	0.63	0.8	53	49	47	45	52	49	47	45	51	48	46	45	50	48	46	45	44					
		否	0.56	1.0	55	52	50	48	54	51	49	48	53	51	49	48	52	50	49	47	46					
				1.25	57	54	52	50	56	54	52	50	55	53	51	50	54	52	51	50	49					
下方投影面積		c m ²		1.5	58	56	54	52	57	55	53	52	56	54	53	52	55	54	52	51	50					
等価発光面積		c m ²		2.0	60	58	56	55	59	57	56	54	58	56	55	54	57	55	54	53	52					
取付 高さ	器具間隔最大限			2.5	61	59	58	56	60	58	57	56	59	57	56	55	58	57	56	55	54					
	横方向 (A)		縦方向 (B)	3.0	61	60	59	57	61	59	58	57	59	58	57	56	58	57	56	56	54					
H m	0.47 H m		0.47 H m	4.0	62	61	60	59	61	60	59	59	60	59	59	58	59	58	58	57	56					
				5.0	63	62	61	60	62	61	60	60	61	60	59	59	59	59	58	58	56					
				7.0	63	63	62	61	63	62	61	61	61	61	60	60	60	60	59	59	57					
				10.0	64	63	63	62	63	63	62	62	62	61	61	61	60	60	60	59	58					

