

| 屋内照明器具特性 |                                      |
|----------|--------------------------------------|
| 品番 (品名)  | L G B 1 5 1 5 1                      |
| 光源       | LLD40402CQ1 ( KAKUSAN ) ×1 860.0 l m |
| 管理番号     | K0184437 ( 0 ) DR 1                  |
| B Z 分類   | BZ3 / 1.4 / BZ4                      |

| 器具効率     |                     | 40 %             | 反射率    | 天井               | 80 %                |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|----------|---------------------|------------------|--------|------------------|---------------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|          |                     |                  |        | 壁                | 70                  | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|          |                     |                  |        | 床                | 10 %                |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|          |                     |                  |        | 室指数              | 照明率 ( X0.01 ) Z C M |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率      |                     | 良<br>中<br>否      | 0.67   | 0.6              | 24                  | 20 | 17 | 16 | 24   | 20 | 17 | 16 | 23   | 19 | 17 | 15 | 22   | 19 | 17 | 15 | 15  |
|          |                     |                  | 0.63   | 0.8              | 28                  | 24 | 21 | 19 | 27   | 24 | 21 | 19 | 26   | 23 | 21 | 19 | 25   | 22 | 20 | 19 | 18  |
|          |                     |                  | 0.56   | 1.0              | 30                  | 27 | 24 | 22 | 30   | 26 | 24 | 22 | 28   | 26 | 23 | 22 | 27   | 25 | 23 | 21 | 20  |
|          |                     |                  |        | 1.25             | 32                  | 29 | 27 | 25 | 32   | 29 | 26 | 24 | 30   | 28 | 26 | 24 | 29   | 27 | 25 | 24 | 23  |
| 下方投影面積   |                     | c m <sup>2</sup> |        | 1.5              | 34                  | 31 | 28 | 26 | 33   | 30 | 28 | 26 | 32   | 29 | 28 | 26 | 31   | 29 | 27 | 26 | 25  |
|          |                     |                  | 等価発光面積 | c m <sup>2</sup> | 2.0                 | 36 | 33 | 31 | 29   | 35 | 33 | 31 | 29   | 34 | 32 | 30 | 29   | 33 | 31 | 29 | 28  |
| 取付<br>高さ | 器具間隔最大限             |                  |        | 2.5              | 37                  | 35 | 33 | 31 | 36   | 34 | 33 | 31 | 35   | 33 | 32 | 30 | 34   | 32 | 31 | 30 | 29  |
|          | 横方向 ( A ) 縦方向 ( B ) |                  |        | 3.0              | 38                  | 36 | 34 | 33 | 37   | 35 | 34 | 32 | 36   | 34 | 33 | 32 | 35   | 33 | 32 | 31 | 30  |
| H m      | 0.95 H m 0.95 H m   |                  |        | 4.0              | 39                  | 37 | 36 | 35 | 38   | 37 | 36 | 34 | 37   | 36 | 35 | 34 | 36   | 35 | 34 | 33 | 32  |
|          |                     |                  |        | 5.0              | 40                  | 38 | 37 | 36 | 39   | 38 | 37 | 36 | 38   | 37 | 36 | 35 | 36   | 36 | 35 | 34 | 33  |
|          |                     |                  |        | 7.0              | 40                  | 39 | 38 | 38 | 40   | 39 | 38 | 37 | 38   | 38 | 37 | 36 | 37   | 37 | 36 | 35 | 34  |
|          |                     |                  |        | 10.0             | 41                  | 40 | 39 | 39 | 40   | 40 | 39 | 38 | 39   | 38 | 38 | 37 | 38   | 37 | 37 | 37 | 35  |

