

屋内照明器具特性	
品番 (品名)	LGB15377
光源	LLD3020MLCE1 ×1 795.0 lm
管理番号	K0176242 (0) DR1
BZ分類	BZ1

器具効率		63 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		0 %	室指数	照明率 (X0.01)																			
下方光束		63 %		Z C M																			
保守率		良	0.67	0.6	51	47	45	43	51	47	45	43	50	47	45	43	49	46	44	43	42		
		中	0.63	0.8	55	52	49	47	55	51	49	47	54	51	49	47	53	50	48	47	46		
		否	1.0	58	54	52	50	57	54	52	50	56	53	51	50	55	53	51	49	49			
			0.56	1.25	60	57	54	53	59	56	54	52	58	55	54	52	57	55	53	52	51		
下方投影面積		c m ²		1.5	61	58	56	54	60	58	56	54	59	57	55	54	58	56	55	53	52		
等価発光面積		c m ²		2.0	63	60	59	57	62	60	58	57	61	59	58	56	59	58	57	56	55		
取付 高さ	器具間隔最大限			2.5	64	62	60	59	63	61	60	59	62	60	59	58	60	59	58	57	56		
	横方向 (A)		縦方向 (B)	3.0	64	63	61	60	64	62	61	60	62	61	60	59	61	60	59	58	57		
H m	0.47 H m		0.47 H m	4.0	65	64	63	62	65	63	62	61	63	62	61	61	62	61	60	60	58		
				5.0	66	65	64	63	65	64	63	62	64	63	62	62	62	62	61	61	59		
				7.0	66	66	65	64	66	65	64	64	64	64	63	63	63	63	62	62	60		
				10.0	67	66	66	65	66	66	65	65	65	64	64	64	63	63	63	62	61		

