

屋内照明器具特性	
品番 (品名)	LGB15377
光源	LLD2000MLCE1 ×1 531.0 lm
管理番号	K0176240 (0) DR 1
BZ分類	BZ5

器具効率		62 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																
保守率		良 中 否	0.67	0.6	35	28	23	20	34	28	23	20	33	27	23	20	31	26	22	19	18
			0.63	0.8	41	34	30	26	40	34	29	26	38	33	29	26	37	32	28	25	24
			0.56	1.0	45	39	34	31	44	38	34	31	42	37	33	30	40	36	32	30	28
				1.25	49	43	39	35	48	42	38	35	46	41	37	35	44	40	37	34	32
下方投影面積		cm ²		1.5	52	46	42	39	50	45	42	38	48	44	41	38	46	43	40	37	35
			等価発光面積	cm ²	2.0	55	51	47	44	54	50	46	43	52	48	45	43	49	46	44	42
取付 高さ	器具間隔最大限			2.5	57	53	50	47	56	52	49	47	54	51	48	46	52	49	47	45	43
	横方向 (A)		縦方向 (B)	3.0	59	55	52	50	57	54	52	49	55	53	50	48	53	51	49	47	45
H m	0.84 H m	0.84 H m		4.0	61	58	56	53	59	57	55	53	57	55	53	52	55	53	52	50	48
				5.0	62	60	58	56	61	59	57	55	58	57	55	54	56	55	54	52	50
				7.0	63	61	60	58	62	60	59	58	60	59	57	56	58	57	56	55	52
				10.0	64	63	62	61	63	62	61	60	61	60	59	58	59	58	57	57	54

