

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 7 7
光源	L L D 3 0 2 0 C U 1 × 1 6 1 5 . 0 l m
管理番号	K 0 1 7 8 7 2 9 (0) D R 1
B Z 分類	B Z 1

器具効率 上方光束 下方光束	5 4 % 0 % 5 4 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
		壁	床	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
		室指数		照明率 (X 0 . 0 1)																Z C M
保守率	良 0 . 6 7	0 . 6	4 4	4 0	3 8	3 6	4 3	4 0	3 8	3 6	4 2	3 9	3 8	3 6	4 2	3 9	3 7	3 6	3 5	
	中 0 . 6 3	0 . 8	4 7	4 4	4 1	4 0	4 6	4 3	4 1	4 0	4 5	4 3	4 1	4 0	4 5	4 2	4 1	3 9	3 9	
	否 0 . 5 6	1 . 0	4 9	4 6	4 4	4 2	4 8	4 6	4 4	4 2	4 7	4 5	4 3	4 2	4 6	4 4	4 3	4 2	4 1	
下方投影面積 等価発光面積	c m ² c m ²	1 . 2 5	5 1	4 8	4 6	4 4	5 0	4 8	4 6	4 4	4 9	4 7	4 5	4 4	4 8	4 6	4 5	4 4	4 3	
		1 . 5	5 2	4 9	4 8	4 6	5 1	4 9	4 7	4 6	5 0	4 8	4 7	4 6	4 9	4 8	4 6	4 5	4 4	
		2 . 0	5 3	5 1	5 0	4 8	5 3	5 1	4 9	4 8	5 1	5 0	4 9	4 8	5 0	4 9	4 8	4 7	4 6	
取付 高さ	器具間隔最大限		2 . 5	5 4	5 2	5 1	5 0	5 4	5 2	5 1	5 0	5 2	5 1	5 0	4 9	5 1	5 0	4 9	4 7	
	横方向 (A)	縦方向 (B)	3 . 0	5 5	5 3	5 2	5 1	5 4	5 3	5 2	5 1	5 3	5 2	5 1	5 0	5 2	5 1	5 0	4 8	
	H m	0 . 4 5 H m	0 . 4 5 H m	4 . 0	5 6	5 4	5 3	5 3	5 5	5 4	5 3	5 2	5 4	5 3	5 2	5 1	5 3	5 2	5 1	4 9
				5 . 0	5 6	5 5	5 4	5 4	5 5	5 5	5 4	5 3	5 4	5 4	5 3	5 2	5 3	5 3	5 2	5 0
				7 . 0	5 7	5 6	5 5	5 5	5 6	5 5	5 5	5 4	5 5	5 4	5 4	5 3	5 4	5 3	5 3	5 1
				1 0 . 0	5 7	5 6	5 6	5 6	5 6	5 5	5 5	5 5	5 5	5 5	5 4	5 4	5 4	5 3	5 3	5 2

