

屋内照明器具特性	
品番 (品名)	LGB15377
光源	LLD4000LCT1 ×1 845.0 lm
管理番号	K0190498 (0) DR 1
BZ分類	BZ5

器具効率		47 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		1 %	室指数	照明率 (X0.01)																		Z	CM
下方光束		46 %																					
保守率		良 中 否	0.67	0.6	27	21	18	15	26	21	17	15	25	20	17	15	24	20	17	15	14		
			0.63	0.8	31	26	22	20	31	26	22	20	29	25	22	19	28	24	21	19	18		
			0.56	1.0	35	30	26	23	34	29	26	23	32	28	25	23	31	27	25	22	21		
			1.25	37	33	29	27	36	32	29	26	35	31	28	26	33	30	28	26	24			
下方投影面積 等価発光面積		cm ² cm ²	1.5	39	35	32	29	38	34	31	29	37	33	31	29	35	32	30	28	27			
			2.0	42	38	35	33	41	38	35	33	39	36	34	32	38	35	33	32	30			
			2.5	43	40	38	36	42	40	37	35	41	38	36	35	39	37	36	34	32			
取付 高さ	器具間隔最大限		3.0	45	42	40	38	44	41	39	37	42	40	38	37	40	39	37	36	34			
	横方向 (A)	縦方向 (B)	4.0	46	44	42	40	45	43	42	40	43	42	40	39	42	41	39	38	37			
H m	0.82 H m	0.82 H m	5.0	47	45	44	42	46	44	43	42	44	43	42	41	43	42	41	40	38			
			7.0	48	47	45	44	47	46	45	44	45	44	44	43	44	43	42	42	40			
			10.0	49	48	47	46	48	47	46	45	46	46	45	44	45	44	44	43	41			

