

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 7 7
光源	LLD2000LCT1 ×1 531.0 lm
管理番号	K0190499 (0) DR 1
B Z 分類	BZ5

器具効率		56 % 上方光束 3 % 下方光束 53 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.67	0.6	32	25	21	18	31	25	20	18	29	24	20	17	28	23	20	17	16
			0.63	0.8	37	31	26	23	36	30	26	23	34	29	26	23	33	28	25	23	21
			1.0	41	35	30	27	40	34	30	27	38	33	29	27	36	32	29	26	25	
			0.56	1.25	44	38	34	31	43	38	34	31	41	37	33	31	39	35	33	30	29
下方投影面積		c m ²	1.5	46	41	37	34	45	40	37	34	43	39	36	34	41	38	35	33	31	
等価発光面積			c m ²	2.0	49	45	42	39	48	44	41	39	46	43	40	38	44	41	39	37	35
取付高さ				器具間隔最大限		2.5	51	48	45	42	50	47	44	42	48	45	43	41	46	44	42
H m		0.82 H m	0.82 H m	3.0	52	49	47	44	51	48	46	44	49	47	45	43	47	45	44	42	40
H m		0.82 H m	0.82 H m	4.0	54	52	49	48	53	51	49	47	51	49	47	46	49	48	46	45	43
				5.0	55	53	51	50	54	52	51	49	52	51	49	48	50	49	48	47	45
				7.0	56	55	53	52	55	54	53	51	53	52	51	50	52	51	50	49	47
				10.0	57	56	55	54	56	55	54	53	54	54	53	52	53	52	51	51	48

