

屋内照明器具特性		
品番 (品名)	L G B 1 5 3 7 7	
光源	L L D 2 0 2 0 L C T 1 × 1 4 6 0 . 0 l m	
管理番号	K 0 1 9 0 5 0 0 (0) D R 1	
B Z 分類	B Z 1	

器具効率		7 5 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		7 5 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束																						
保守率		良 中 否	0 . 6	6 1	5 6	5 3	5 1	6 1	5 6	5 3	5 1	6 0	5 6	5 3	5 1	5 9	5 5	5 3	5 1	5 0		
			0 . 8	6 6	6 1	5 8	5 6	6 5	6 1	5 8	5 6	6 4	6 0	5 8	5 6	6 3	6 0	5 7	5 6	5 5		
			1 . 0	6 9	6 5	6 2	5 9	6 8	6 4	6 1	5 9	6 7	6 3	6 1	5 9	6 5	6 3	6 0	5 9	5 8		
			0 . 5 6																			
下方投影面積 等価発光面積		c m ² c m ²	1 . 2 5	7 1	6 7	6 5	6 3	7 0	6 7	6 4	6 2	6 9	6 6	6 4	6 2	6 8	6 5	6 3	6 2	6 1		
			1 . 5	7 3	6 9	6 7	6 5	7 2	6 9	6 7	6 5	7 0	6 8	6 6	6 4	6 9	6 7	6 5	6 4	6 3		
			2 . 0	7 5	7 2	7 0	6 8	7 4	7 1	6 9	6 8	7 2	7 0	6 9	6 7	7 1	6 9	6 8	6 7	6 5		
取付 高さ	器具間隔最大限		2 . 5	7 6	7 4	7 2	7 0	7 5	7 3	7 1	7 0	7 4	7 2	7 0	6 9	7 2	7 1	6 9	6 8	6 7		
	横方向 (A) 縦方向 (B)		3 . 0	7 7	7 5	7 3	7 2	7 6	7 4	7 3	7 1	7 4	7 3	7 2	7 1	7 3	7 2	7 1	7 0	6 8		
H m	0 . 4 5 H m 0 . 4 5 H m		4 . 0	7 8	7 6	7 5	7 4	7 7	7 6	7 5	7 3	7 6	7 4	7 3	7 2	7 4	7 3	7 2	7 1	7 0		
			5 . 0	7 9	7 7	7 6	7 5	7 8	7 7	7 6	7 5	7 6	7 5	7 4	7 4	7 5	7 4	7 3	7 3	7 1		
			7 . 0	7 9	7 9	7 8	7 7	7 9	7 8	7 7	7 6	7 7	7 6	7 6	7 5	7 5	7 5	7 4	7 4	7 2		
			1 0 . 0	8 0	7 9	7 9	7 8	7 9	7 9	7 8	7 8	7 7	7 7	7 7	7 6	7 6	7 5	7 5	7 5	7 3		

