

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 7 8
光源	LLD2000LCE1 ×1 531.0 lm
管理番号	K0176250 (0) DR 1
B Z 分類	BZ5 / 0.7 / BZ4 / 2.3 / BZ5

器具効率		60 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		2 %	室指数	照明率 (X0.01)																		Z	C		M
下方光束		58 %																							
保守率		良 中 否	0.67	0.6	35	28	23	20	34	27	23	20	32	26	22	20	31	26	22	19	18				
			0.63	0.8	41	34	29	26	40	33	29	26	38	32	28	25	36	31	28	25	24				
			0.56	1.0	44	38	34	30	43	38	33	30	41	36	33	30	40	35	32	29	28				
				1.25	48	42	38	35	47	42	38	34	45	40	37	34	43	39	36	33	32				
下方投影面積		cm ²	1.5	50	45	41	38	49	44	41	38	47	43	40	37	45	42	39	36	35					
等価発光面積		cm ²	2.0	54	49	46	43	52	48	45	42	50	47	44	42	48	45	43	41	39					
取付 高さ	器具間隔最大限		2.5	56	52	49	46	54	51	48	46	52	49	47	45	50	48	46	44	42					
	横方向 (A)		縦方向 (B)		3.0	57	54	51	49	56	53	50	48	54	51	49	47	52	50	48	46	44			
H m	0.85 H m	0.85 H m	4.0	59	56	54	52	58	55	53	51	56	54	52	50	54	52	51	49	47					
			5.0	60	58	56	54	59	57	55	54	57	55	54	52	55	54	52	51	49					
			7.0	61	60	58	57	60	59	57	56	58	57	56	55	56	55	54	53	51					
			10.0	62	61	60	59	61	60	59	58	59	58	58	57	57	57	56	55	53					

