

# 屋内照明器具特性

品番 (品名)	LSEB5724		
光源	LED5000_70_500 ×1	500.0 lm	
管理番号	K0160344(0)D 1		
BZ分類	BZ1		

器具効率	100%	天井	80%				70%				50%				30%				0%				
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
下方光束	100%	床		10%				10%				10%				10%				0%			
室指数	照明率 ( X0.01 )																			ZCM			
保守率	良 0.67	0.6	0.6	85	79	75	73	84	79	75	72	83	78	75	72	82	77	74	72	71			
	中 0.63		0.8	90	85	81	78	89	84	81	78	88	83	80	78	86	83	80	78	77			
	否 0.56		1.0	93	88	85	82	92	88	85	82	91	87	84	82	89	86	83	81	80			
下方投影面積	cm <sup>2</sup>	等価発光面積	cm <sup>2</sup>	1.25	96	92	89	86	95	91	88	86	93	90	87	85	92	89	87	85	83		
				1.5	98	94	91	89	97	94	91	89	95	92	90	88	94	91	89	87	86	86	
取付高さ	器具間隔最大限		Hm	0.37Hm	0.37Hm	2.5	102	99	97	95	101	99	97	95	99	97	95	94	97	96	94	93	91
	横方向 (A)	縦方向 (B)				3.0	103	101	99	97	102	100	98	97	100	98	97	95	98	97	95	94	92
Hm	0.37Hm	0.37Hm	4.0	104	103	101	100	103	102	100	99	101	100	99	98	99	98	97	96	94	94		
			5.0	105	104	102	101	104	103	102	100	102	101	100	99	100	99	98	97	95	95	95	
Hm	0.37Hm	0.37Hm	7.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	99	99	96	96		
			10.0	107	106	105	105	106	105	104	104	103	103	102	102	101	101	100	100	97	97		

