

屋内照明器具特性	
品番（品名）	L G B 1 5 3 7 8
光源	L L D 2 0 2 0 C U 1 × 1 4 6 8 . 0 l m
管理番号	K 0 1 7 8 7 3 6 （ 0 ） D R 1
B Z 分類	B Z 1

器具効率	6 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
			壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
			床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束	6 0 %	室指数	照明率 (X 0 . 0 1)																		Z C M	
下方光束	6 0 %		良 中 否	0 . 6	4 9	4 5	4 3	4 1	4 9	4 5	4 3	4 1	4 8	4 5	4 3	4 1	4 7	4 4	4 2	4 1	4 0	
保守率	0 . 6 7				0 . 8	5 3	4 9	4 7	4 5	5 2	4 9	4 7	4 5	5 1	4 8	4 6	4 5	5 0	4 8	4 6	4 5	4 4
	0 . 6 3	1 . 0			5 5	5 2	4 9	4 8	5 4	5 1	4 9	4 8	5 3	5 1	4 9	4 7	5 2	5 0	4 8	4 7	4 6	
下方投影面積	c m ²	1 . 2 5	5 7	5 4	5 2	5 0	5 6	5 4	5 2	5 0	5 5	5 3	5 1	5 0	5 4	5 2	5 1	4 9	4 8			
等価発光面積			c m ²	1 . 5	5 8	5 5	5 3	5 2	5 7	5 5	5 3	5 2	5 6	5 4	5 3	5 1	5 5	5 3	5 2	5 1	5 0	
			2 . 0	6 0	5 8	5 6	5 4	5 9	5 7	5 5	5 4	5 8	5 6	5 5	5 4	5 7	5 5	5 4	5 3	5 2		
取付 高さ	器具間隔最大限		2 . 5	6 1	5 9	5 7	5 6	6 0	5 8	5 7	5 6	5 9	5 7	5 6	5 5	5 7	5 6	5 5	5 5	5 3		
	横方向 (A)		縦方向 (B)		3 . 0	6 1	6 0	5 8	5 7	6 1	5 9	5 8	5 7	5 9	5 8	5 7	5 6	5 8	5 7	5 6	5 4	
H m	0 . 4 6 H m	0 . 4 6 H m	4 . 0	6 2	6 1	6 0	5 9	6 1	6 0	5 9	5 8	6 0	5 9	5 8	5 8	5 9	5 8	5 7	5 7	5 6		
			5 . 0	6 3	6 2	6 1	6 0	6 2	6 1	6 0	5 9	6 1	6 0	5 9	5 9	5 9	5 9	5 8	5 8	5 6		
			7 . 0	6 3	6 2	6 2	6 1	6 2	6 2	6 1	6 1	6 1	6 1	6 0	6 0	6 0	5 9	5 9	5 9	5 7		
			1 0 . 0	6 4	6 3	6 3	6 2	6 3	6 2	6 2	6 2	6 2	6 1	6 1	6 0	6 0	6 0	6 0	5 9	5 8		

