

屋内照明器具特性	
品番 (品名)	LSEW4062
光源	LED5000_70_1010 x1 1010.0 1m
管理番号	K0161585(0)DB1
BZ分類	BZ6/0.7/BZ5/3.5/BZ6/4.5/BZ5/6.0/BZ6

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	14%	床	10%				10%				10%				10%				0%	
下方光束	86%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	53	40	32	27	51	39	31	26	47	37	30	25	43	35	29	24	21
	中	0.6	0.8	62	50	42	36	60	49	41	35	55	46	39	34	51	43	37	33	29
	否	0.56	1.0	68	57	49	43	66	55	48	42	61	52	46	41	57	49	43	39	35
			1.25	74	64	56	50	71	62	55	49	66	58	52	47	62	55	50	45	41
下方投影面積		cm ²	1.5	78	69	61	55	76	67	60	54	70	63	57	52	65	59	54	50	45
等価発光面積		cm ²	2.0	84	76	69	64	81	74	67	62	76	69	64	60	70	65	61	57	52
取付高さ	器具間隔最大限		2.5	88	80	74	69	85	78	73	68	79	74	69	65	74	69	66	62	57
	横方向 (A)	縦方向 (B)	3.0	90	84	78	74	87	81	76	72	82	77	73	69	76	72	69	66	60
H _m	1.31H _m	1.31H _m	4.0	94	88	84	80	91	86	82	78	85	81	78	74	80	77	74	71	65
			5.0	96	91	87	84	93	89	85	82	87	84	81	78	82	79	77	74	68
			7.0	98	95	92	89	95	92	89	87	90	87	85	83	84	82	80	79	72
			10.0	100	97	95	93	97	95	93	91	92	90	88	86	87	85	84	82	76

