

屋内照明器具特性	
品番 (品名)	LGB15378
光源	LLD2000LCT1 ×1 531.0 lm
管理番号	K0190502 (0) DR1
BZ分類	BZ5/0.7/BZ4/2.3/BZ5

器具効率		50 %	反射率	天井	80 %				70 %				50 %				30 %				0 %					
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %				10 %				10 %				10 %				0 %					
上方光束		2 %	室指数	照明率 (X0.01)																			Z	C		M
下方光束		48 %																								
保守率		良 中 否	0.67	0.6	29	23	19	16	28	22	19	16	27	22	18	16	25	21	18	16	15					
			0.63	0.8	34	28	24	21	33	28	24	21	31	27	23	21	30	26	23	21	20					
			1.0	37	32	28	25	36	31	28	25	34	30	27	25	33	29	26	24	23						
			0.56	1.25	40	35	31	29	39	34	31	28	37	33	30	28	35	32	30	28	26					
下方投影面積		cm ²	1.5	42	37	34	31	41	37	34	31	39	36	33	31	37	34	32	30	29						
等価発光面積		cm ²	2.0	44	41	38	35	43	40	37	35	42	39	36	34	40	38	36	34	32						
取付 高さ	器具間隔最大限		2.5	46	43	40	38	45	42	40	38	43	41	39	37	42	40	38	36	35						
	横方向 (A)		縦方向 (B)		3.0	47	44	42	40	46	44	42	40	44	42	41	39	43	41	40	38	37				
H m	0.85 H m		0.85 H m		4.0	49	47	45	43	48	46	44	42	46	44	43	42	44	43	42	41	39				
				5.0	50	48	46	45	49	47	46	44	47	46	44	43	45	44	43	42	40					
				7.0	51	49	48	47	50	49	47	46	48	47	46	45	47	46	45	44	42					
				10.0	51	51	50	49	51	50	49	48	49	48	48	47	47	47	46	46	44					

