

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 7 9
光源	LLD2000LCE1 ×1 531.0 l m
管理番号	K0176219 (0) DR 1
B Z 分類	B Z 5

器具効率		85 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		3 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束		82 %																						
保守率		良 中 否	0.67	0.6	47	37	30	26	46	36	30	25	44	35	29	25	41	34	29	25	23			
			0.63	0.8	55	46	39	34	54	45	38	34	51	43	38	33	49	42	37	33	31			
			0.56	1.0	61	52	45	40	59	51	45	40	56	49	44	39	54	47	43	39	36			
				1.25	66	58	51	46	64	57	51	46	61	55	49	45	58	53	48	44	42			
下方投影面積		c m ²	1.5	70	62	56	51	68	61	55	51	65	59	54	50	62	57	52	49	46				
等価発光面積			c m ²	2.0	74	68	62	58	73	67	62	58	69	64	60	56	67	62	59	55	53			
取付 高さ	器具間隔最大限		2.5	77	72	67	63	76	71	66	62	73	68	64	61	70	66	63	60	57				
	横方向 (A)		縦方向 (B)		3.0	80	75	70	67	78	73	69	66	75	71	68	65	72	69	66	63	60		
H m	1.15 H m		1.15 H m		4.0	82	78	75	72	81	77	74	71	78	75	72	69	75	72	70	68	65		
					5.0	84	81	78	75	82	79	77	74	79	77	75	72	77	74	73	71	68		
					7.0	86	83	81	79	84	82	80	78	81	80	78	76	79	77	76	74	71		
					10.0	87	86	84	82	86	84	83	81	83	82	80	79	80	79	78	77	74		

