

屋内照明器具特性	
品番 (品名)	LGB15390
光源	LLD4000MLCE1 ×1 845.0 lm
管理番号	K0176263 (0) DR1
BZ分類	BZ4/3.5/BZ5

器具効率		50 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01)																			Z C M	
保守率		良 中 否	0.67	0.6	29	23	20	17	28	23	20	17	27	22	19	17	26	22	19	17	16				
			0.63	0.8	34	28	25	22	33	28	24	22	32	27	24	22	30	26	24	21	20				
			0.56	1.0	37	32	28	25	36	31	28	25	34	30	27	25	33	29	27	25	23				
				1.25	40	35	32	29	39	34	31	29	37	33	31	28	36	32	30	28	27				
下方投影面積		cm ²		1.5	42	37	34	31	41	37	34	31	39	36	33	31	37	35	32	30	29				
			等価発光面積	cm ²	2.0	44	41	38	35	43	40	37	35	42	39	37	35	40	38	36	34	32			
取付 高さ	器具間隔最大限			2.5	46	43	40	38	45	42	40	38	43	41	39	37	42	40	38	36	35				
	横方向 (A)		縦方向 (B)	3.0	47	44	42	40	46	44	42	40	44	42	41	39	43	41	40	38	37				
H m	0.99 H m		0.99 H m	4.0	49	46	45	43	48	46	44	42	46	44	43	42	44	43	42	41	39				
				5.0	49	48	46	45	49	47	46	44	47	46	44	43	45	44	43	42	41				
				7.0	51	49	48	47	50	48	47	46	48	47	46	45	47	46	45	44	42				
				10.0	51	50	49	49	51	50	49	48	49	48	48	47	47	47	46	46	44				

