

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 9 0
光源	L L D 3 0 2 0 C U 1 × 1 6 1 5 . 0 l m
管理番号	K 0 1 7 8 7 4 0 (0) D R 1
B Z 分類	B Z 1

器具効率		5 4 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		5 4 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束																							
保守率		良 中 否	0 . 6	4 3	4 0	3 8	3 6	4 3	4 0	3 8	3 6	4 2	3 9	3 7	3 6	4 2	3 9	3 7	3 6	3 5			
			0 . 8	4 7	4 4	4 1	4 0	4 6	4 3	4 1	4 0	4 5	4 3	4 1	4 0	4 5	4 2	4 1	4 0	3 9			
			1 . 0	4 9	4 6	4 4	4 2	4 8	4 6	4 4	4 2	4 7	4 5	4 3	4 2	4 7	4 5	4 3	4 2	4 1			
			0 . 5 6	1 . 2 5	5 1	4 8	4 6	4 5	5 0	4 8	4 6	4 5	4 9	4 7	4 5	4 4	4 8	4 6	4 5	4 4	4 3		
下方投影面積		c m ²	1 . 5	5 2	5 0	4 8	4 6	5 1	4 9	4 7	4 6	5 0	4 8	4 7	4 6	4 9	4 8	4 6	4 5	4 5			
			等価発光面積	c m ²	2 . 0	5 3	5 1	5 0	4 9	5 3	5 1	5 0	4 8	5 2	5 0	4 9	4 8	5 1	4 9	4 8	4 7	4 7	
取付 高さ	器具間隔最大限		2 . 5	5 4	5 3	5 1	5 0	5 4	5 2	5 1	5 0	5 3	5 1	5 0	4 9	5 1	5 0	5 0	4 9	4 8			
	横方向 (A)		縦方向 (B)		3 . 0	5 5	5 3	5 2	5 1	5 4	5 3	5 2	5 1	5 3	5 2	5 1	5 0	5 2	5 1	5 0	4 9		
H m	0 . 4 9 H m		0 . 4 9 H m		4 . 0	5 6	5 5	5 4	5 3	5 5	5 4	5 3	5 2	5 4	5 3	5 2	5 3	5 2	5 1	5 1	5 0		
					5 . 0	5 6	5 5	5 4	5 4	5 5	5 5	5 4	5 3	5 4	5 4	5 3	5 2	5 3	5 3	5 2	5 0		
					7 . 0	5 7	5 6	5 5	5 5	5 6	5 5	5 5	5 4	5 5	5 4	5 4	5 3	5 4	5 3	5 3	5 1		
					1 0 . 0	5 7	5 7	5 6	5 6	5 6	5 6	5 6	5 5	5 5	5 5	5 4	5 4	5 4	5 3	5 3	5 2		

