

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 9 0
光源	L L D 2 0 0 0 1 C Q 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 8 6 4 8 2 (0) D R 1
B Z 分類	B Z 5

器具効率	5 7 % 上方光束 2 % 下方光束 5 5 %	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
		反射率	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
		室指数	照明率 (X 0 . 0 1) Z C M																
保守率	良 0 . 6 7	0 . 6	3 3	2 6	2 1	1 8	3 2	2 5	2 1	1 8	3 0	2 5	2 1	1 8	2 9	2 4	2 0	1 8	1 7
	中 0 . 6 3	0 . 8	3 8	3 2	2 7	2 4	3 7	3 1	2 7	2 4	3 5	3 0	2 6	2 4	3 4	2 9	2 6	2 3	2 2
	否 0 . 5 6	1 . 0	4 2	3 6	3 2	2 8	4 1	3 5	3 1	2 8	3 9	3 4	3 1	2 8	3 7	3 3	3 0	2 7	2 6
		1 . 2 5	4 5	4 0	3 6	3 2	4 4	3 9	3 5	3 2	4 2	3 8	3 4	3 2	4 0	3 7	3 4	3 1	3 0
下方投影面積 等価発光面積	c m ² c m ²	1 . 5	4 8	4 3	3 9	3 6	4 7	4 2	3 8	3 5	4 4	4 0	3 7	3 5	4 2	3 9	3 6	3 4	3 2
		2 . 0	5 1	4 7	4 3	4 0	5 0	4 6	4 3	4 0	4 8	4 4	4 2	3 9	4 6	4 3	4 0	3 8	3 7
		2 . 5	5 3	4 9	4 6	4 4	5 2	4 8	4 6	4 3	5 0	4 7	4 4	4 2	4 8	4 5	4 3	4 1	4 0
		3 . 0	5 4	5 1	4 8	4 6	5 3	5 0	4 8	4 5	5 1	4 9	4 6	4 4	4 9	4 7	4 5	4 4	4 2
取付高さ	器具間隔最大限 横方向 (A) 縦方向 (B)	4 . 0	5 6	5 3	5 1	4 9	5 5	5 3	5 0	4 9	5 3	5 1	4 9	4 8	5 1	4 9	4 8	4 6	4 4
H m	0 . 8 2 H m 0 . 8 2 H m	5 . 0	5 7	5 5	5 3	5 1	5 6	5 4	5 2	5 1	5 4	5 2	5 1	4 9	5 2	5 1	4 9	4 8	4 6
		7 . 0	5 8	5 7	5 5	5 4	5 7	5 6	5 4	5 3	5 5	5 4	5 3	5 2	5 3	5 2	5 1	5 1	4 8
		1 0 . 0	5 9	5 8	5 7	5 6	5 8	5 7	5 6	5 5	5 6	5 5	5 5	5 4	5 4	5 4	5 3	5 2	5 0

