

屋内照明器具特性	
品番 (品名)	LGB15390
光源	LLD4000LCT1 ×1 845.0 lm
管理番号	K0190504 (0) DR 1
BZ分類	BZ4 / 2.3 / BZ5

器具効率		47 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
				室指数																			
			照明率 (X0.01)																			ZCM	
保守率		良 中 否	0.67	0.6	28	22	19	16	27	22	19	16	26	22	18	16	25	21	18	16	15		
			0.63	0.8	32	27	23	21	31	27	23	21	30	26	23	21	29	25	22	20	19		
			0.56	1.0	35	30	27	24	34	30	26	24	33	29	26	24	31	28	25	23	22		
				1.25	38	33	30	27	37	33	30	27	35	32	29	27	34	31	28	27	25		
下方投影面積		cm ²	1.5	40	36	32	30	39	35	32	30	37	34	31	29	36	33	31	29	28			
等価発光面積		cm ²	2.0	42	39	36	34	41	38	36	33	40	37	35	33	38	36	34	32	31			
取付 高さ	器具間隔最大限		2.5	44	41	38	36	43	40	38	36	41	39	37	35	40	38	36	35	33			
	横方向 (A) 縦方向 (B)		3.0	45	42	40	38	44	42	40	38	42	40	39	37	41	39	38	36	35			
Hm	1.00Hm	1.00Hm	4.0	46	44	42	41	45	44	42	40	44	42	41	40	42	41	40	39	37			
			5.0	47	45	44	42	46	45	43	42	45	43	42	41	43	42	41	40	39			
			7.0	48	47	46	45	47	46	45	44	46	45	44	43	44	44	43	42	40			
			10.0	49	48	47	46	48	47	46	46	47	46	45	45	45	45	44	44	42			

