

| 屋内照明器具特性 |                         |
|----------|-------------------------|
| 品番 (品名)  | LGB15390                |
| 光源       | LLD2000LCT1 ×1 531.0 lm |
| 管理番号     | K0190505 ( 0 ) DR 1     |
| BZ分類     | BZ4/2.3/BZ5             |

| 器具効率           |                     | 56 %                | 反射率       | 天井            | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |   |   |  |   |
|----------------|---------------------|---------------------|-----------|---------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|---|---|--|---|
|                |                     |                     |           | 壁             | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |   |   |  |   |
|                |                     |                     |           | 床             | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |   |   |  |   |
| 上方光束           |                     | 2 %                 | 室指数       | 照明率 ( X0.01 ) |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     | Z | C |  | M |
| 下方光束           |                     | 54 %                |           |               |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |   |   |  |   |
| 保守率            |                     | 良<br>中<br>否         | 0.67      | 0.6           | 33   | 26 | 22 | 19 | 32   | 26 | 22 | 19 | 31   | 25 | 22 | 19 | 29   | 25 | 21 | 19 | 18  |   |   |  |   |
|                |                     |                     | 0.63      | 0.8           | 38   | 32 | 28 | 25 | 37   | 31 | 27 | 24 | 35   | 30 | 27 | 24 | 34   | 30 | 26 | 24 | 23  |   |   |  |   |
|                |                     |                     | 0.56      | 1.0           | 41   | 36 | 31 | 28 | 40   | 35 | 31 | 28 | 39   | 34 | 31 | 28 | 37   | 33 | 30 | 28 | 26  |   |   |  |   |
|                |                     |                     |           | 1.25          | 44   | 39 | 35 | 32 | 43   | 39 | 35 | 32 | 41   | 37 | 34 | 32 | 40   | 36 | 34 | 31 | 30  |   |   |  |   |
| 下方投影面積         |                     | cm <sup>2</sup>     | 1.5       | 46            | 42   | 38 | 35 | 45 | 41   | 38 | 35 | 44 | 40   | 37 | 34 | 42 | 39   | 36 | 34 | 32 |     |   |   |  |   |
| 等価発光面積         |                     | cm <sup>2</sup>     | 2.0       | 49            | 45   | 42 | 40 | 48 | 45   | 42 | 39 | 47 | 43   | 41 | 39 | 45 | 42   | 40 | 38 | 36 |     |   |   |  |   |
| 取付<br>高さ       | 器具間隔最大限             |                     | 2.5       | 51            | 48   | 45 | 43 | 50 | 47   | 44 | 42 | 48 | 46   | 43 | 41 | 47 | 44   | 42 | 41 | 39 |     |   |   |  |   |
|                | 横方向 ( A )           |                     | 縦方向 ( B ) | 3.0           | 53   | 50 | 47 | 45 | 52   | 49 | 46 | 44 | 50   | 47 | 45 | 44 | 48   | 46 | 44 | 43 | 41  |   |   |  |   |
| H <sub>m</sub> | 1.00 H <sub>m</sub> | 1.00 H <sub>m</sub> | 4.0       | 54            | 52   | 50 | 48 | 53 | 51   | 49 | 47 | 51 | 50   | 48 | 46 | 50 | 48   | 47 | 46 | 44 |     |   |   |  |   |
|                |                     |                     | 5.0       | 55            | 53   | 52 | 50 | 54 | 53   | 51 | 49 | 53 | 51   | 50 | 48 | 51 | 50   | 48 | 47 | 45 |     |   |   |  |   |
|                |                     |                     | 7.0       | 57            | 55   | 54 | 52 | 56 | 54   | 53 | 52 | 54 | 53   | 52 | 51 | 52 | 51   | 50 | 49 | 48 |     |   |   |  |   |
|                |                     |                     | 10.0      | 57            | 56   | 55 | 54 | 57 | 56   | 55 | 54 | 55 | 54   | 53 | 52 | 53 | 52   | 52 | 51 | 49 |     |   |   |  |   |

