

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 9 1
光源	LLD4000LCE1 ×1 845.0 l m
管理番号	K0176269 (0) DR 1
B Z 分類	BZ4 / 6.0 / BZ5

器具効率		51 % 上方光束 1 % 下方光束 50 %	反射率	天井	80 %					70 %					50 %					30 %					0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %					10 %					10 %					10 %					0 %
						室指数	照明率 (X0.01) Z C M																			
保守率		良 中 否	0.67	0.6	30	24	21	18	30	24	21	18	28	24	20	18	27	23	20	18	17					
			0.63	0.8	35	29	26	23	34	29	25	23	33	28	25	23	31	27	25	22	21					
			0.56	1.0	38	33	29	26	37	32	29	26	36	32	28	26	34	31	28	26	25					
				1.25	41	36	33	30	40	36	32	30	38	35	32	29	37	34	31	29	28					
下方投影面積		c m ² c m ²		1.5	43	39	35	33	42	38	35	32	40	37	34	32	39	36	34	32	30					
等価発光面積				2.0	46	42	39	37	45	41	39	36	43	40	38	36	41	39	37	35	34					
				2.5	47	44	42	39	46	43	41	39	45	42	40	38	43	41	39	38	36					
取付	器具間隔最大限			2.5	47	44	42	39	46	43	41	39	45	42	40	38	43	41	39	38	36					
高さ																								横方向 (A)		縦方向 (B)
H m	0.96 H m		0.96 H m	4.0	50	48	46	44	49	47	45	44	47	46	44	43	46	44	43	42	40					
				5.0	51	49	47	46	50	48	47	46	48	47	46	45	47	46	45	44	42					
				7.0	52	51	49	48	51	50	49	48	49	48	48	47	48	47	46	46	44					
				10.0	53	52	51	50	52	51	50	49	50	50	49	48	49	48	48	47	45					

