

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 9 1
光源	L L D 3 0 2 0 L C E 1 × 1 7 9 5 . 0 l m
管理番号	K 0 1 7 6 2 7 2 (0) D R 1
B Z 分類	B Z 1

器具効率		6 5 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		0 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		6 5 %																				
保守率		良	0 . 6 7	0 . 6	5 4	4 9	4 7	4 5	5 3	4 9	4 7	4 5	5 2	4 9	4 6	4 5	5 1	4 8	4 6	4 5	4 4	
		中	0 . 6 3	0 . 8	5 8	5 4	5 1	4 9	5 7	5 4	5 1	4 9	5 6	5 3	5 1	4 9	5 5	5 2	5 0	4 9	4 8	
		否	0 . 5 6	1 . 0	6 0	5 7	5 4	5 2	5 9	5 6	5 4	5 2	5 8	5 6	5 4	5 2	5 7	5 5	5 3	5 2	5 1	
		1 . 2 5	6 2	5 9	5 7	5 5	6 1	5 9	5 7	5 5	6 0	5 8	5 6	5 5	5 9	5 7	5 6	5 4	5 3			
下方投影面積		c m ²		1 . 5	6 4	6 1	5 9	5 7	6 3	6 0	5 8	5 7	6 2	5 9	5 8	5 6	6 0	5 9	5 7	5 6	5 5	
等価発光面積		c m ²		2 . 0	6 5	6 3	6 1	6 0	6 5	6 3	6 1	5 9	6 3	6 2	6 0	5 9	6 2	6 1	5 9	5 8	5 7	
取付 高さ	器具間隔最大限		2 . 5	6 6	6 4	6 3	6 2	6 6	6 4	6 2	6 1	6 4	6 3	6 2	6 1	6 3	6 2	6 1	6 0	5 9		
	横方向 (A) 縦方向 (B)		3 . 0	6 7	6 5	6 4	6 3	6 6	6 5	6 4	6 2	6 5	6 4	6 3	6 2	6 4	6 3	6 2	6 1	6 0		
H m	0 . 4 7 H m	0 . 4 7 H m	4 . 0	6 8	6 7	6 6	6 5	6 7	6 6	6 5	6 4	6 6	6 5	6 4	6 3	6 5	6 4	6 3	6 2	6 1		
			5 . 0	6 9	6 8	6 7	6 6	6 8	6 7	6 6	6 5	6 6	6 6	6 5	6 4	6 5	6 4	6 4	6 3	6 2		
			7 . 0	6 9	6 8	6 8	6 7	6 8	6 8	6 7	6 6	6 7	6 6	6 6	6 5	6 6	6 5	6 5	6 4	6 3		
			1 0 . 0	7 0	6 9	6 9	6 8	6 9	6 8	6 8	6 7	6 7	6 7	6 7	6 6	6 6	6 6	6 5	6 5	6 3		

