

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 9 1
光源	L L D 2 0 0 0 L C T 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 9 0 5 0 9 (0) D R 1
B Z 分類	B Z 4 / 6 . 0 / B Z 5

器具効率		5 0 %		反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
					壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
					床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
					照明率 (X 0 . 0 1) Z C M																					
保守率		良 中 否	0 . 6 7	0 . 6	3 0	2 4	2 0	1 8	2 9	2 4	2 0	1 8	2 8	2 3	2 0	1 8	2 7	2 2	2 0	1 7	1 7					
			0 . 6 3	0 . 8	3 4	2 9	2 5	2 3	3 4	2 8	2 5	2 2	3 2	2 8	2 5	2 2	3 1	2 7	2 4	2 2	2 1					
			0 . 5 6	1 . 0	3 7	3 2	2 9	2 6	3 6	3 2	2 8	2 6	3 5	3 1	2 8	2 6	3 4	3 0	2 7	2 5	2 4					
				1 . 2 5	4 0	3 6	3 2	2 9	3 9	3 5	3 2	2 9	3 8	3 4	3 1	2 9	3 6	3 3	3 1	2 9	2 7					
下方投影面積		c m ²	1 . 5	4 2	3 8	3 5	3 2	4 1	3 7	3 4	3 2	3 9	3 6	3 4	3 1	3 8	3 5	3 3	3 1	3 0						
			2 . 0	4 5	4 1	3 8	3 6	4 4	4 1	3 8	3 6	4 2	3 9	3 7	3 5	4 1	3 8	3 6	3 5	3 3						
取付高さ	器具間隔最大限		2 . 5	4 6	4 3	4 1	3 9	4 5	4 3	4 0	3 8	4 4	4 1	3 9	3 8	4 2	4 0	3 9	3 7	3 6						
	横方向 (A) 縦方向 (B)		3 . 0	4 7	4 5	4 3	4 1	4 7	4 4	4 2	4 0	4 5	4 3	4 1	4 0	4 3	4 2	4 0	3 9	3 7						
H m	0 . 9 6 H m	0 . 9 6 H m	4 . 0	4 9	4 7	4 5	4 3	4 8	4 6	4 4	4 3	4 6	4 5	4 3	4 2	4 5	4 4	4 2	4 1	4 0						
			5 . 0	5 0	4 8	4 7	4 5	4 9	4 7	4 6	4 5	4 7	4 6	4 5	4 4	4 6	4 5	4 4	4 3	4 1						
			7 . 0	5 1	5 0	4 8	4 7	5 0	4 9	4 8	4 7	4 9	4 8	4 7	4 6	4 7	4 6	4 5	4 5	4 3						
			1 0 . 0	5 2	5 1	5 0	4 9	5 1	5 0	4 9	4 8	4 9	4 9	4 8	4 7	4 8	4 7	4 7	4 6	4 4						

