

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 9 1
光源	L L D 2 0 2 0 L C T 1 × 1 4 6 0 . 0 l m
管理番号	K 0 1 9 0 5 1 0 (0) D R 1
B Z 分類	B Z 1

器具効率			7 3 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %				
					壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %				
上方光束			0 %	室指数	照明率 (X 0 . 0 1)																			Z C M		
下方光束			7 3 %																							
保守率			良 中 否	0 . 6 7	0 . 6	6 0	5 5	5 2	5 0	5 9	5 5	5 2	5 0	5 8	5 5	5 2	5 0	5 8	5 4	5 2	5 0	4 9				
				0 . 6 3	0 . 8	6 4	6 0	5 7	5 5	6 4	6 0	5 7	5 5	6 3	5 9	5 7	5 5	6 2	5 9	5 7	5 5	5 4				
				0 . 5 6	1 . 0	6 7	6 3	6 1	5 9	6 6	6 3	6 0	5 9	6 5	6 2	6 0	5 8	6 4	6 2	6 0	5 8	5 7				
				1 . 2 5	6 9	6 6	6 4	6 2	6 9	6 6	6 3	6 2	6 7	6 5	6 3	6 1	6 6	6 4	6 2	6 1	6 0					
下方投影面積			c m ²	1 . 5	7 1	6 8	6 6	6 4	7 0	6 8	6 5	6 4	6 9	6 7	6 5	6 3	6 8	6 6	6 4	6 3	6 2					
				2 . 0	7 3	7 1	6 9	6 7	7 2	7 0	6 8	6 7	7 1	6 9	6 7	6 6	6 9	6 8	6 7	6 5	6 4					
等価発光面積			c m ²	2 . 5	7 4	7 2	7 0	6 9	7 3	7 2	7 0	6 9	7 2	7 0	6 9	6 8	7 0	6 9	6 8	6 7	6 6					
				3 . 0	7 5	7 3	7 2	7 0	7 4	7 3	7 1	7 0	7 3	7 1	7 0	6 9	7 1	7 0	6 9	6 8	6 7					
H m	0 . 4 7 H m		0 . 4 7 H m	4 . 0	7 6	7 5	7 3	7 2	7 5	7 4	7 3	7 2	7 4	7 3	7 2	7 1	7 2	7 1	7 1	7 0	6 8					
				5 . 0	7 7	7 6	7 5	7 4	7 6	7 5	7 4	7 3	7 4	7 3	7 3	7 2	7 3	7 2	7 1	7 1	6 9					
				7 . 0	7 7	7 7	7 6	7 5	7 6	7 6	7 5	7 4	7 5	7 4	7 4	7 3	7 3	7 3	7 2	7 2	7 0					
				1 0 . 0	7 8	7 7	7 7	7 6	7 7	7 6	7 6	7 6	7 5	7 5	7 5	7 4	7 4	7 4	7 3	7 3	7 1					

