

屋内照明器具特性	
品番 (品名)	L G C 3 1 1 2 D
光源	LED6500_70_3800 ×1 3800.0 lm
管理番号	K0172085 (0) D 1
B Z 分類	B Z 5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		2 %	室指数	照明率 (X 0 . 0 1)																		Z C M	
下方光束		9 8 %																					
保守率		良 中 否	0 . 6 3	0 . 6	0 . 5 6	0 . 6	5 7	4 4	3 7	3 1	5 5	4 4	3 6	3 1	5 3	4 3	3 6	3 1	5 0	4 1	3 5	3 1	2 9
			0 . 6	0 . 8	6 7	5 5	4 7	4 1	6 5	5 4	4 7	4 1	6 2	5 3	4 6	4 1	5 9	5 1	4 5	4 1	3 8		
			0 . 5 6	1 . 0	7 3	6 2	5 5	4 9	7 2	6 2	5 4	4 9	6 8	6 0	5 3	4 8	6 6	5 8	5 2	4 8	4 5		
				1 . 2 5	7 9	6 9	6 2	5 6	7 7	6 8	6 2	5 6	7 4	6 6	6 0	5 6	7 1	6 5	5 9	5 5	5 2		
下方投影面積		c m ²	1 . 5	8 3	7 4	6 8	6 2	8 2	7 3	6 7	6 2	7 8	7 1	6 6	6 1	7 5	6 9	6 4	6 0	5 8			
等価発光面積			c m ²	2 . 0	8 9	8 1	7 5	7 0	8 7	8 0	7 5	7 0	8 4	7 8	7 3	6 9	8 1	7 6	7 2	6 8	6 5		
取付 高さ	器具間隔最大限		2 . 5	9 2	8 6	8 1	7 6	9 1	8 5	8 0	7 6	8 7	8 2	7 8	7 4	8 4	8 0	7 6	7 3	7 0			
	横方向 (A)		縦方向 (B)	3 . 0	9 5	8 9	8 5	8 0	9 3	8 8	8 4	8 0	9 0	8 6	8 2	7 8	8 7	8 3	8 0	7 7	7 4		
H m	1 . 2 5 H m	1 . 2 5 H m	4 . 0	9 8	9 4	9 0	8 6	9 6	9 2	8 9	8 5	9 3	9 0	8 7	8 4	9 0	8 7	8 5	8 2	7 9			
			5 . 0	1 0 0	9 6	9 3	9 0	9 8	9 5	9 2	8 9	9 5	9 2	9 0	8 7	9 2	9 0	8 8	8 6	8 3			
			7 . 0	1 0 2	9 9	9 7	9 4	1 0 1	9 8	9 6	9 3	9 8	9 5	9 3	9 2	9 5	9 3	9 1	9 0	8 7			
			1 0 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 2	1 0 0	9 9	9 7	9 9	9 8	9 6	9 5	9 7	9 5	9 4	9 3	9 0			

