

屋内照明器具特性

品番 (品名)	L S E W4 0 6 8				
光源	LED2700_70_765 x1 765.0 l m				
管理番号	K0160460(0)DB1				
BZ分類	BZ5				

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	床	10%				10%				10%				10%				0%
下方光束	100%		室指数	照明率 (X0.01)																ZCM
保守率	良	0.69	0.6	57	45	37	31	55	44	36	31	53	43	36	31	51	42	36	31	29
	中	0.67	0.8	67	55	47	42	65	55	47	42	63	53	46	41	60	52	46	41	39
	否	0.63	1.0	74	63	55	49	72	62	55	49	69	60	54	49	66	59	53	48	46
			1.25	80	70	63	57	78	69	62	57	75	67	61	56	72	65	60	56	53
下方投影面積			1.5	84	75	68	63	82	74	67	62	79	72	66	62	76	70	65	61	59
等価発光面積			2.0	89	82	76	71	88	81	75	71	85	79	74	70	82	77	73	69	67
取付高さ	器具間隔最大限		2.5	93	87	81	77	91	86	81	76	88	83	79	75	85	81	78	74	72
	横方向 (A)	縦方向 (B)	3.0	95	90	85	81	94	89	84	81	91	87	83	79	88	84	81	78	76
Hm	1.27Hm	1.27Hm	4.0	99	94	90	87	97	93	89	86	94	91	88	85	91	89	86	84	81
			5.0	100	97	94	91	99	96	93	90	96	93	91	88	94	91	89	87	84
			7.0	103	100	97	95	101	99	96	94	99	96	95	93	96	94	93	91	88
			10.0	104	102	101	99	103	101	99	98	100	99	97	96	98	97	95	94	91

