

屋内照明器具特性	
品番 (品名)	XLGB1608
光源	LLD2000LCE1 ×1 531.0 lm
管理番号	K0176271 (0) DR1
BZ分類	BZ4/6.0/BZ5

器具効率		60 %	反射率	天井	80 %				70 %				50 %				30 %				0 %					
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %				10 %				10 %				10 %				0 %					
上方光束		1 %	室指数	照明率 (X0.01)																			Z	C		M
下方光束		59 %																								
保守率		良 中 否	0.67	0.6	36	29	25	22	35	29	24	22	34	28	24	21	32	27	24	21	20					
			0.63	0.8	41	35	31	27	41	34	30	27	39	34	30	27	37	33	29	27	25					
			0.56	1.0	45	39	35	31	44	38	34	31	42	37	34	31	41	36	33	31	29					
			1.25	48	43	39	36	47	42	38	35	45	41	38	35	44	40	37	35	33						
下方投影面積		cm ²	1.5	51	46	42	39	50	45	41	38	48	44	41	38	46	43	40	37	36						
等価発光面積		cm ²	2.0	54	50	46	43	53	49	46	43	51	48	45	42	49	46	44	42	40						
取付 高さ	器具間隔最大限		2.5	56	52	49	47	55	52	49	46	53	50	48	46	51	49	47	45	43						
	横方向 (A)		縦方向 (B)		3.0	57	54	52	49	56	53	51	49	54	52	50	48	52	50	49	47	45				
H m	0.96 H m		0.96 H m		4.0	59	57	54	52	58	56	54	52	56	54	52	51	54	53	51	50	48				
					5.0	60	58	56	55	59	57	56	54	57	56	54	53	55	54	53	52	50				
					7.0	61	60	59	57	61	59	58	57	59	57	56	55	57	56	55	54	52				
					10.0	62	61	60	59	61	60	59	59	60	59	58	57	58	57	57	56	54				

