

屋内照明器具特性	
品番 (品名)	XLGB1202
光源	LLD4000LCE1 ×1 845.0 lm
管理番号	K0176245 (0) DR1
BZ分類	BZ5/0.7/BZ4/2.3/BZ5

器具効率		5 1 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
				室指数	照明率 (X 0 . 0 1) Z C M																				
保守率		良 中 否	0 . 6 7	0 . 6	2 9	2 3	1 9	1 7	2 9	2 3	1 9	1 7	2 7	2 2	1 9	1 6	2 6	2 2	1 9	1 6	1 5				
			0 . 6 3	0 . 8	3 4	2 9	2 5	2 2	3 3	2 8	2 4	2 2	3 2	2 7	2 4	2 1	3 0	2 6	2 3	2 1	2 0				
			0 . 5 6	1 . 0	3 7	3 2	2 8	2 6	3 7	3 2	2 8	2 5	3 5	3 1	2 7	2 5	3 3	3 0	2 7	2 5	2 3				
				1 . 2 5	4 0	3 6	3 2	2 9	3 9	3 5	3 2	2 9	3 8	3 4	3 1	2 9	3 6	3 3	3 0	2 8	2 7				
下方投影面積		c m ²	1 . 5	4 2	3 8	3 5	3 2	4 1	3 7	3 4	3 2	4 0	3 6	3 3	3 1	3 8	3 5	3 3	3 1	2 9					
			等価発光面積	c m ²	2 . 0	4 5	4 2	3 9	3 6	4 4	4 1	3 8	3 6	4 2	4 0	3 7	3 5	4 1	3 8	3 6	3 4	3 3			
取付 高さ	器具間隔最大限		2 . 5	4 7	4 4	4 1	3 9	4 6	4 3	4 1	3 9	4 4	4 2	4 0	3 8	4 2	4 0	3 9	3 7	3 5					
	横方向 (A) 縦方向 (B)		3 . 0	4 8	4 5	4 3	4 1	4 7	4 5	4 2	4 1	4 5	4 3	4 1	4 0	4 4	4 2	4 0	3 9	3 7					
H m	0 . 8 5 H m	0 . 8 5 H m	4 . 0	5 0	4 7	4 6	4 4	4 9	4 7	4 5	4 3	4 7	4 5	4 4	4 2	4 5	4 4	4 3	4 1	4 0					
			5 . 0	5 1	4 9	4 7	4 6	5 0	4 8	4 7	4 5	4 8	4 7	4 5	4 4	4 6	4 5	4 4	4 3	4 1					
			7 . 0	5 2	5 0	4 9	4 8	5 1	5 0	4 8	4 7	4 9	4 8	4 7	4 6	4 8	4 7	4 6	4 5	4 3					
			1 0 . 0	5 3	5 2	5 1	5 0	5 2	5 1	5 0	4 9	5 0	4 9	4 9	4 8	4 8	4 8	4 7	4 7	4 5					

