

屋内照明器具特性	
品番 (品名)	LGBZ3407
光源	LED6200_70_5499 x1 5499.0 lm
管理番号	K0154966(0)D 1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	4%	床	10%				10%				10%				10%				0%				
下方光束	96%	室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.63	0.6	5.5	4.2	3.4	2.9	5.3	4.1	3.4	2.8	5.0	4.0	3.3	2.8	4.8	3.9	3.2	2.8	2.6			
	中	0.6	0.8	6.5	5.3	4.5	3.9	6.3	5.2	4.4	3.8	6.0	5.0	4.3	3.8	5.7	4.8	4.2	3.7	3.5			
	否	0.56	1.0	7.1	6.0	5.2	4.6	6.9	5.9	5.1	4.6	6.6	5.7	5.0	4.5	6.2	5.5	4.9	4.4	4.2			
			1.25	7.7	6.7	5.9	5.3	7.5	6.6	5.9	5.3	7.1	6.3	5.7	5.2	6.8	6.1	5.6	5.1	4.8			
下方投影面積	cm <sup>2</sup>		1.5	8.1	7.2	6.5	5.9	7.9	7.1	6.4	5.8	7.5	6.8	6.2	5.7	7.2	6.6	6.1	5.6	5.3			
	等価発光面積		2.0	8.7	7.9	7.3	6.7	8.5	7.8	7.2	6.7	8.1	7.5	7.0	6.5	7.8	7.2	6.8	6.4	6.1			
取付高さ	器具間隔最大限		2.5	9.1	8.4	7.8	7.3	8.9	8.2	7.7	7.2	8.5	7.9	7.5	7.1	8.1	7.7	7.3	6.9	6.6			
	横方向 (A)	縦方向 (B)	3.0	9.3	8.7	8.2	7.7	9.1	8.6	8.1	7.7	8.7	8.3	7.9	7.5	8.4	8.0	7.6	7.3	7.0			
Hm	1.31Hm	1.32Hm	4.0	9.6	9.2	8.7	8.3	9.4	9.0	8.6	8.2	9.1	8.7	8.4	8.0	8.7	8.4	8.1	7.9	7.5			
			5.0	9.8	9.4	9.1	8.7	9.7	9.3	8.9	8.6	9.3	9.0	8.7	8.4	8.9	8.7	8.4	8.2	7.8			
			7.0	10.1	9.8	9.5	9.2	9.9	9.6	9.3	9.1	9.5	9.3	9.1	8.9	9.2	9.0	8.8	8.6	8.3			
			10.0	10.3	10.0	9.8	9.6	10.1	9.9	9.7	9.5	9.7	9.6	9.4	9.2	9.4	9.3	9.1	9.0	8.6			

