

屋内照明器具特性	
品番 (品名)	XL553PHTK
光源	LED3000_85_1700 ×1 1700.0 lm
管理番号	K0130720 (0) DB 1
BZ分類	BZ5 / 0.7 / BZ4

器具効率		100 % 上方光束 0 % 下方光束	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01) ZCM															
保守率		良 中 否	0.6	58	46	38	33	57	45	38	33	54	44	38	33	52	43	37	33	31		
			0.8	68	57	49	44	67	56	49	44	64	55	48	43	62	54	48	43	41		
			1.0	75	64	57	52	73	64	57	51	70	62	56	51	68	61	55	51	49		
			1.25	81	71	65	59	79	71	64	59	76	69	63	58	74	67	62	58	56		
下方投影面積		cm ²	1.5	85	76	70	65	83	75	69	64	80	74	68	64	78	72	67	63	61		
			等価発光面積		cm ²	2.0	90	83	78	73	89	82	77	73	86	80	76	72	83	78	75	71
取付 高さ	器具間隔最大限		2.5	94	88	83	79	92	87	82	78	89	85	81	77	87	83	79	76	74		
	横方向 (A) 縦方向 (B)		3.0	96	91	87	83	95	90	86	82	92	88	84	81	89	86	83	80	78		
H m	1.25 H m	1.25 H m	4.0	99	95	92	88	98	94	91	88	95	92	89	86	92	90	87	85	83		
			5.0	101	98	95	92	100	96	94	91	97	94	92	90	94	92	90	88	86		
			7.0	103	101	98	96	102	99	97	95	99	97	95	94	97	95	94	92	89		
			10.0	105	103	101	100	103	102	100	99	101	99	98	97	98	97	96	95	92		

