

屋内照明器具特性	
品番 (品名)	NNF 4 1 5 0 2
光源	LED3500_85_3890 ×1 3890.0 lm
管理番号	K0172825 (0) DR 1
B Z 分類	BZ6

器具効率		1 0 0 % 上方光束 2 0 % 下方光束 8 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1)																Z C M
保守率		良 中 否	0 . 8 3	0 . 6	5 1	3 9	3 1	2 5	4 9	3 7	3 0	2 5	4 4	3 5	2 8	2 3	4 0	3 2	2 6	2 2	1 9
			0 . 8 1	0 . 8	6 0	4 8	4 0	3 4	5 8	4 7	3 9	3 3	5 3	4 3	3 7	3 2	4 8	4 0	3 4	3 0	2 6
			0 . 7 7	1 . 0	6 7	5 5	4 7	4 1	6 4	5 3	4 6	4 0	5 8	4 9	4 3	3 8	5 3	4 6	4 0	3 6	3 1
				1 . 2 5	7 3	6 2	5 4	4 8	6 9	6 0	5 2	4 7	6 3	5 5	4 9	4 4	5 8	5 1	4 6	4 2	3 7
下方投影面積		c m ²	1 . 5	7 7	6 7	5 9	5 3	7 3	6 4	5 8	5 2	6 7	6 0	5 4	4 9	6 1	5 5	5 0	4 6	4 1	
			等価発光面積	c m ²	2 . 0	8 2	7 4	6 7	6 2	7 9	7 1	6 5	6 0	7 2	6 6	6 1	5 6	6 6	6 1	5 7	5 3
取付 高さ	器具間隔最大限		2 . 5	8 6	7 9	7 3	6 7	8 2	7 6	7 0	6 5	7 6	7 0	6 6	6 2	6 9	6 5	6 1	5 8	5 1	
	横方向 (A)		縦方向 (B)	3 . 0	8 9	8 2	7 7	7 2	8 5	7 9	7 4	7 0	7 8	7 3	6 9	6 5	7 2	6 8	6 5	6 1	5 5
1 . 5m	2 . 2 6 m	2 . 2 4 m	4 . 0	9 2	8 7	8 2	7 8	8 8	8 4	7 9	7 5	8 2	7 8	7 4	7 1	7 5	7 2	6 9	6 6	5 9	
2	2 . 9 5	2 . 7 4	5 . 0	9 4	9 0	8 5	8 2	9 0	8 6	8 3	7 9	8 4	8 0	7 7	7 4	7 7	7 5	7 2	7 0	6 2	
2 . 5	3 . 6 6	3 . 2 9	7 . 0	9 6	9 3	9 0	8 7	9 3	9 0	8 7	8 4	8 6	8 4	8 1	7 9	8 0	7 8	7 6	7 4	6 6	
3	4 . 3 7	3 . 8 5	1 0 . 0	9 8	9 6	9 3	9 1	9 5	9 3	9 0	8 8	8 8	8 6	8 4	8 3	8 2	8 0	7 9	7 7	6 9	

