

屋内照明器具特性	
品番 (品名)	NNF 4 0 9 0 1
光源	LED4000_85_2370 ×1 2370.0 lm
管理番号	K0172825 (0) DR 1
B Z 分類	BZ6

器具効率		100 % 上方光束 20 % 下方光束 80 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01) Z CM															
保守率		良 中 否	0.83	0.6	51	39	31	25	49	37	30	25	44	35	28	23	40	32	26	22	19	
			0.81	0.8	60	48	40	34	58	47	39	33	53	43	37	32	48	40	34	30	26	
			0.77	1.0	67	55	47	41	64	53	46	40	58	49	43	38	53	46	40	36	31	
			0.77	1.25	73	62	54	48	69	60	52	47	63	55	49	44	58	51	46	42	37	
下方投影面積		cm ²	1.5	77	67	59	53	73	64	58	52	67	60	54	49	61	55	50	46	41		
等価発光面積			cm ²	2.0	82	74	67	62	79	71	65	60	72	66	61	56	66	61	57	53	47	
				2.5	86	79	73	67	82	76	70	65	76	70	66	62	69	65	61	58	51	
取付 高さ	器具間隔最大限			3.0	89	82	77	72	85	79	74	70	78	73	69	65	72	68	65	61	55	
	横方向 (A) 縦方向 (B)		4.0		92	87	82	78	88	84	79	75	82	78	74	71	75	72	69	66	59	
1.5m	2.2 m	1.97 m	4.0	92	87	82	78	88	84	79	75	82	78	74	71	75	72	69	66	59		
2	2.9	2.54	5.0	94	90	85	82	90	86	83	79	84	80	77	74	77	75	72	70	62		
2.5	3.61	3.12	7.0	96	93	90	87	93	90	87	84	86	84	81	79	80	78	76	74	66		
3	4.33	3.72	10.0	98	96	93	91	95	93	90	88	88	86	84	83	82	80	79	77	69		

