

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 9 2
光源	LLD2000LCE1 ×1 531.0 l m
管理番号	K0175769 (0) DR 1
B Z 分類	B Z 1

器具効率		53 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.67	0.6	41	38	35	33	41	37	35	33	40	37	35	33	39	37	35	33	33
			0.63	0.8	45	42	40	38	45	42	39	38	44	41	39	38	43	41	39	38	37
			0.56	1.0	48	45	42	41	47	44	42	41	46	44	42	41	45	43	42	40	40
				1.25	50	47	45	44	49	47	45	43	48	46	44	43	47	45	44	43	42
下方投影面積		c m ²		1.5	51	49	47	45	50	48	47	45	49	47	46	45	48	47	46	45	44
			等価発光面積	c m ²	2.0	52	51	49	48	52	50	49	48	51	49	48	47	50	49	48	47
取付 高さ	器具間隔最大限			2.5	53	52	50	49	53	51	50	49	52	50	49	49	51	50	49	48	47
	横方向 (A) 縦方向 (B)			3.0	54	53	51	50	53	52	51	50	52	51	50	50	51	50	50	49	48
H m	0.65 H m 0.65 H m			4.0	55	54	53	52	54	53	52	52	53	52	52	51	52	51	51	50	49
				5.0	55	54	54	53	55	54	53	52	53	53	52	52	52	52	51	51	50
				7.0	56	55	54	54	55	55	54	53	54	53	53	53	53	52	52	52	50
				10.0	56	56	55	55	55	55	55	54	54	54	54	53	53	53	53	52	51

