

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 9 2
光源	L L D 2 0 0 0 1 C Q 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 7 5 6 5 2 (0) D R 1
B Z 分類	B Z 1

器具効率		5 1 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	4 0	3 6	3 4	3 2	3 9	3 6	3 4	3 2	3 9	3 5	3 3	3 2	3 8	3 5	3 3	3 2	3 1
			0 . 6 3	0 . 8	4 4	4 0	3 8	3 6	4 3	4 0	3 8	3 6	4 2	4 0	3 8	3 6	4 1	3 9	3 7	3 6	3 5
			0 . 5 6	1 . 0	4 6	4 3	4 1	3 9	4 5	4 3	4 1	3 9	4 4	4 2	4 0	3 9	4 4	4 2	4 0	3 9	3 8
				1 . 2 5	4 8	4 5	4 3	4 2	4 7	4 5	4 3	4 2	4 6	4 4	4 3	4 1	4 5	4 4	4 2	4 1	4 0
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	4 9	4 7	4 5	4 4	4 8	4 6	4 5	4 3	4 7	4 6	4 4	4 3	4 6	4 5	4 4	4 3	4 2	
			2 . 0	5 0	4 9	4 7	4 6	5 0	4 8	4 7	4 6	4 9	4 8	4 6	4 5	4 8	4 7	4 6	4 5	4 4	
			2 . 5	5 1	5 0	4 9	4 8	5 1	4 9	4 8	4 7	5 0	4 9	4 8	4 7	4 9	4 8	4 7	4 6	4 5	
取付 高さ	器具間隔最大限		3 . 0	5 2	5 1	5 0	4 9	5 1	5 0	4 9	4 8	5 0	4 9	4 8	4 8	4 9	4 9	4 8	4 7	4 6	
	横方向 (A)	縦方向 (B)	4 . 0	5 3	5 2	5 1	5 0	5 2	5 1	5 0	5 0	5 1	5 0	5 0	4 9	5 0	4 9	4 9	4 8	4 7	
H m	0 . 7 0 H m	0 . 7 0 H m	5 . 0	5 3	5 2	5 2	5 1	5 3	5 2	5 1	5 1	5 1	5 1	5 0	5 0	5 0	5 0	4 9	4 9	4 8	
			7 . 0	5 4	5 3	5 2	5 2	5 3	5 3	5 2	5 2	5 2	5 1	5 1	5 1	5 1	5 1	5 0	5 0	4 9	
			1 0 . 0	5 4	5 4	5 3	5 3	5 3	5 3	5 3	5 2	5 2	5 2	5 2	5 1	5 1	5 1	5 1	5 0	4 9	

