

# 屋内照明器具特性

品番 (品名)	LGB15344				
光源	LDA13L-G/Z100E/S/W ×1      1520.0   1 m				
管理番号	K0167837(1)DB1				
BZ分類	BZ5				

器具効率	94%	天井	80%				70%				50%				30%				0%		
	上方光束		30%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		64%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.67	0.6	4.9	3.8	3.1	2.6	4.6	3.6	3.0	2.5	4.1	3.3	2.8	2.4	3.7	3.0	2.5	2.2	1.8	
	中	0.63	0.8	5.8	4.8	4.1	3.5	5.5	4.5	3.9	3.4	4.9	4.1	3.6	3.2	4.3	3.7	3.3	2.9	2.5	
	否	0.56	1.0	6.4	5.4	4.7	4.2	6.0	5.2	4.5	4.0	5.4	4.7	4.2	3.8	4.8	4.2	3.8	3.5	2.9	
			1.25	6.9	6.0	5.4	4.8	6.5	5.7	5.1	4.7	5.8	5.2	4.7	4.3	5.2	4.7	4.3	4.0	3.3	
下方投影面積	c m <sup>2</sup>		1.5	7.3	6.5	5.8	5.3	6.9	6.1	5.6	5.1	6.1	5.6	5.1	4.7	5.5	5.0	4.6	4.3	3.6	
	等価発光面積		c m <sup>2</sup>	2.0	7.8	7.1	6.5	6.0	7.3	6.7	6.2	5.8	6.6	6.1	5.7	5.3	5.8	5.5	5.1	4.9	4.1
取付高さ	器具間隔最大限		2.5	8.1	7.5	6.9	6.5	7.6	7.1	6.6	6.2	6.8	6.4	6.0	5.7	6.1	5.8	5.5	5.2	4.4	
	横方向 (A)	縦方向 (B)	3.0	8.3	7.7	7.3	6.9	7.8	7.4	7.0	6.6	7.0	6.7	6.3	6.0	6.3	6.0	5.7	5.5	4.6	
H m	1.62 H m	1.62 H m	4.0	8.5	8.1	7.7	7.4	8.1	7.7	7.4	7.1	7.3	7.0	6.7	6.5	6.5	6.3	6.1	5.9	4.9	
			5.0	8.7	8.4	8.0	7.7	8.3	8.0	7.7	7.4	7.5	7.2	7.0	6.7	6.7	6.5	6.3	6.1	5.2	
			7.0	8.9	8.6	8.4	8.1	8.5	8.2	8.0	7.8	7.7	7.5	7.3	7.1	6.9	6.7	6.6	6.4	5.4	
			10.0	9.1	8.9	8.7	8.5	8.7	8.5	8.3	8.1	7.8	7.7	7.5	7.4	7.0	6.9	6.8	6.7	5.6	

