

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 9 2
光源	L L D 2 0 0 0 L C T 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 9 0 4 6 9 (0) D R 1
B Z 分類	B Z 1

器具効率		4 8 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
						照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	3 8	3 4	3 2	3 0	3 7	3 4	3 2	3 0	3 7	3 4	3 2	3 0	3 6	3 3	3 2	3 0	3 0	
			0 . 6 3	0 . 8	4 1	3 8	3 6	3 5	4 1	3 8	3 6	3 5	4 0	3 8	3 6	3 4	3 9	3 7	3 6	3 4	3 4	
			0 . 5 6	1 . 0	4 3	4 1	3 9	3 7	4 3	4 0	3 9	3 7	4 2	4 0	3 8	3 7	4 1	3 9	3 8	3 7	3 6	
				1 . 2 5	4 5	4 3	4 1	4 0	4 5	4 3	4 1	4 0	4 4	4 2	4 0	3 9	4 3	4 1	4 0	3 9	3 8	
下方投影面積		c m ²	1 . 5	4 6	4 4	4 3	4 1	4 6	4 4	4 2	4 1	4 5	4 3	4 2	4 1	4 4	4 3	4 2	4 1	4 0		
			2 . 0	4 8	4 6	4 5	4 4	4 7	4 6	4 4	4 3	4 6	4 5	4 4	4 3	4 5	4 4	4 3	4 3	4 2		
等価発光面積		c m ²	2 . 5	4 9	4 7	4 6	4 5	4 8	4 7	4 6	4 5	4 7	4 6	4 5	4 4	4 6	4 5	4 5	4 4	4 3		
			3 . 0	4 9	4 8	4 7	4 6	4 9	4 8	4 7	4 6	4 8	4 7	4 6	4 5	4 7	4 6	4 5	4 5	4 4		
H m	0 . 6 5 H m		0 . 6 5 H m	4 . 0	5 0	4 9	4 8	4 7	4 9	4 9	4 8	4 7	4 8	4 8	4 7	4 6	4 7	4 7	4 6	4 5		
				5 . 0	5 0	5 0	4 9	4 8	5 0	4 9	4 8	4 8	4 9	4 8	4 8	4 7	4 8	4 7	4 7	4 6		
				7 . 0	5 1	5 0	5 0	4 9	5 0	5 0	4 9	4 9	4 9	4 9	4 8	4 8	4 8	4 8	4 8	4 7		
				1 0 . 0	5 1	5 1	5 0	5 0	5 1	5 0	5 0	5 0	4 9	4 9	4 9	4 9	4 8	4 8	4 8	4 7		

