

屋内照明器具特性	
品番 (品名)	L G B 1 6 7 0 2
光源	L L D 2 0 0 0 L C E 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 7 5 7 6 9 (0) D R 1
B Z 分類	B Z 1

器具効率		53 %	反射率	天井	80 %					70 %					50 %					30 %					0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %					10 %					10 %					10 %					0 %	
上方光束		0 %	室指数	照明率 (X0.01)																				Z	C	M
下方光束		53 %																								
保守率		良 中 否	0.67	0.6	41	38	35	33	41	37	35	33	40	37	35	33	39	37	35	33	33					
			0.63	0.8	45	42	40	38	45	42	39	38	44	41	39	38	43	41	39	38	37					
			0.56	1.0	48	45	42	41	47	44	42	41	46	44	42	41	45	43	42	40	40					
				1.25	50	47	45	44	49	47	45	43	48	46	44	43	47	45	44	43	42					
下方投影面積		cm ²	1.5	51	49	47	45	50	48	47	45	49	47	46	45	48	47	46	45	44						
等価発光面積		cm ²	2.0	52	51	49	48	52	50	49	48	51	49	48	47	50	49	48	47	46						
取付高さ	器具間隔最大限		2.5	53	52	50	49	53	51	50	49	52	50	49	49	51	50	49	48	47						
	横方向 (A)	縦方向 (B)	3.0	54	53	51	50	53	52	51	50	52	51	50	50	51	50	50	49	48						
H m	0.65 H m	0.65 H m	4.0	55	54	53	52	54	53	52	52	53	52	52	51	52	51	51	50	49						
			5.0	55	54	54	53	55	54	53	52	53	53	52	52	52	52	51	51	50						
			7.0	56	55	54	54	55	55	54	53	54	53	53	53	53	52	52	52	50						
			10.0	56	56	55	55	55	55	55	54	54	54	54	53	53	53	53	52	51						

